



UP01DTCNLA04 Product Details



UP01DTCNLA04
(1-1825043-1)

TE Internal Number: 1-1825043-1



Active

[View 3D PDF](#)

Snap Action Switches



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Switch Style = Ultra Miniature
- Actuator Style = Lever, Normal
- Termination Type = Printed Circuit Board Right
- Single Pole - Double Throw Configuration (Pole-Throw)
- Contact Rating = 0.1A

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [SWITCH, SNAP ACTION, ULTRAMINIATURE](#) (PDF, English)

Catalog Pages/Data Sheets:

- [SWITCHES_CORE_PROGRAM_CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version B1)
- [3D Model](#) (IGES, Version B1)
- [3D Model](#) (STEP, Version B1)

[List all Documents](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Actuator Style = Lever, Normal
- Mount Angle = Right Angle

Electrical Characteristics:

- Contact Rating = 0.1A

Termination Features:

- Termination Type = Printed Circuit Board Right

Dimensions:

- Pre Travel (mm [in]) = 3.00 [0.118]

Body Features:

- Switch Style = Ultra Miniature
- Releasing Force (g [oz]) = 8 [0.282]
- Operating Position (mm [in]) = 7.90 [0.311]
- Over Travel (mm [in]) = 0.60 [0.024]
- Movement Differential (mm [in]) = 0.80 [0.031]

Contact Features:

- Contact Base Material = Brass
- Contact Plating = Gold over Nickel

Housing Features:

- Housing Material = Nylon - GF

Configuration Features:

- Configuration (Pole-Throw) = Single Pole - Double Throw

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

- Operating Force (g [oz]) = 50 [1.764]

Other:

- Brand = TE Connectivity

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility
Plan](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Knowledge Base](#)

[Manage Your Account](#)

