

## FSM4JH Product Details



Share



Print



Email



### FSM4JH

(3-1437565-9)

TE Internal Number: 3-1437565-9

Superseded

[Search for Replacement Parts](#)

### Pushbutton Switches



Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Switch
- Tactile
- Contact Rating = 50mA
- Operating Function = Off [On]
- Not Ganged

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)



[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- [SWITCHES\\_CORE\\_PROGRAM\\_CATALOG](#) (PDF, English)

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Switch
- Mount Angle = Vertical
- Actuator Style = Round

#### Electrical Characteristics:

- Contact Rating = 50mA

#### Termination Features:

- Termination Type = Printed Circuit

#### Dimensions:

- Actuator Length (mm [in]) = 1.40 [0.055]
- Switch Height (mm [in]) = 5.00 [0.196]

#### Body Features:

- Mount Style = Through-Hole
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = Polyamide
- Actuator Material = Polyacetal Resin

#### Contact Features:

- Contact Plating = Silver
- Contact Base Material = Copper Alloy

#### Housing Features:

- Process Sealed = No
- Low Profile = No

#### Configuration Features:

- Tactile = Yes
- Operating Function = Off [On]
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without
- Tactile Feel = With

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- Temperature Rating = High

#### Operation/Application:

- Actuator Force (g [oz]) = 160.00 [5.648]

#### Packaging Features:

- Packaging Method = Loose Piece

#### Other:

- [Series](#) = FSMJ
- Brand = Alcoswitch
- Comment = (On) indicates momentary position.

## Corporate Information

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)  
[Terms & Conditions](#)  
[Privacy Policy](#)  
[AODA Accessibility Policy](#)  
[AODA Multi-Year Accessibility Plan](#)

## Quick Links

[Distributor Inventory](#)  
[Product Cross Reference](#)  
[Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

## Customer Support

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Knowledge Base](#)  
[Manage Your Account](#)

## Keep Me Informed

