




4-1553349-9 Product Details



4-1553349-9

TE Internal Number: 4-1553349-9
[Active](#)

Fiber Optic Cable

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Region = Asia, Latin America, North America
- Indoor Application, Indoor/Outdoor Application, Outdoor Application
- Armoring = None
- OFNP (Plenum) Jacket
- 24 Fibers

[View all Features](#)

Quick Links

- [Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [INDOOR/OUTDOOR FIBER OPTIC CABLE CUSTOMER SPECIFICATION \(PDF, English\)](#)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

- Installation Tensile Strength (Newton [lb_f]) = 2670.0 [600]

Electrical Characteristics:

- Max Attenuation @ 850nm (dB/km) = 3.2
- Max Attenuation @ 1300nm (dB/km) = 1.2

Termination Features:

- Fiber Type (Micron) = OM4 50/125

Dimensions:

- Installation Bend Radius (mm [in]) = 190.00 [7.480]

Body Features:

- Armoring = None
- Cable Construction = 5 x 12
- Cable Color = Aqua
- Nominal Outside Diameter (mm [in]) = 9.30 [0.3361]
- Long Term Bend Radius (mm [in]) = 90 [3.54]
- Nominal Weight (kg/km) = 82
- Nominal Weight (lbs/1000ft) = 55
- Long Term Tensile Strength (Newton [lb_f]) = 890.0 [200]

Configuration Features:

- Number of Fibers = 24
- Cable Buffering = Loose Tube - Dry

Industry Standards:

- [Flammability Rating Type](#) = OFNP (Plenum) Jacket
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Agency/Standard = ANSI/TIA-568, ANSI/TIA-472E000, ICEA S-104-696
- Applicable Fiber Specification = IEC 60793-2-10 A1a.3, TIA-492AAAD

Environmental:

- Storage Temperature (°C [°F]) = -40 - +70 [-40 - +158]
- Operating Temperature (°C [°F]) = -40 - +70 [-40 - +158]

Conditions for Usage:

- Installation Temperature (°C [°F]) = -10 - +60 [14 - 140]
- Minimum Overfilled Launch Bandwidth @ 850nm (MHz*km) = 3500
- Minimum Overfilled Launch Bandwidth @ 1300nm (MHz*km) = 500
- Minimum Effective Modal Bandwidth @ 850nm (MHz*km) = 4700
- Minimum 10Gb Ethernet Transmission Distance @ 850nm (M) = 550

Operation/Application:

- Application = Indoor, Indoor/Outdoor, Outdoor

Product Availability:

- Region = Asia, North America, Latin America

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

