




1-1553325-1 Product Details



1-1553325-1

TE Internal Number: 1-1553325-1



Fiber Optic Cable

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Region = Asia, Latin America, North America
- Indoor Application
- Armoring = None
- OFNR (Riser) Jacket
- 96 Fibers

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [Premise Distribution Optical Cable Customer Specific...](#) (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Mechanical Attachment:

- Installation Tensile Strength (Newton [lb_f]) = 1320.0 [297]

Electrical Characteristics:

- Max Attenuation @ 850nm (dB/km) = 3.5
- Max Attenuation @ 1300nm (dB/km) = 1.2

Termination Features:

- Fiber Type (Micron) = OM1 62.5/125

Dimensions:

- Installation Bend Radius (mm [in]) = 462.00 [18.200]

Body Features:

- Armoring = None
- Cable Construction = 8 x 12
- Cable Color = Orange
- Nominal Outside Diameter (mm [in]) = 22.80 [0.8976]
- Long Term Bend Radius (mm [in]) = 231 [9.1]
- Nominal Weight (kg/km) = 433
- Nominal Weight (lbs/1000ft) = 291
- Long Term Tensile Strength (Newton [lb_f]) = 396.0 [89]

Configuration Features:

- Number of Fibers = 96
- Cable Buffering = Tight Buffered

Industry Standards:

- [Flammability Rating Type](#) = OFNR (Riser) Jacket
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Agency/Standard = ANSI/ICEA S-83-596, ANSI/TIA-568, Telcordia GR-409-CORE
- Applicable Fiber Specification = IEC 60793-2-10 A1b, TIA-492AAAA

Environmental:

- Storage Temperature (°C [°F]) = -40 - +70 [-40 - +158]
- Operating Temperature (°C [°F]) = -20 - +70 [-4 - +158]

Conditions for Usage:

- Installation Temperature (°C [°F]) = -10 - +60 [14 - 140]
- Minimum Overfilled Launch Bandwidth @ 850nm (MHz*km) = 200
- Minimum Overfilled Launch Bandwidth @ 1300nm (MHz*km) = 500
- Minimum 10Gb Ethernet Transmission Distance @ 850nm (M) = 33

Operation/Application:

- Application = Indoor

Product Availability:

- Region = Asia, North America, Latin America

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

