This browser does not have Java enabled.

HSC20024RJ Product Details

Share Print Email



HSC20024RJ
(5-1630019-1)
TE Internal Number: 5-1630019-1
Active

View 3D PDF

Fixed Resistors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Fixed Resistor
- Resistor Type = Power Resistor
- Resistance Selection = <1K Ω
- Resistance = 24 Ω
- Power Rating = 200.00 W

View all Features

Add to My Part List | Request Sample | Find Similar Products | Buy Product

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- HSC200 ALUMINIUM HOUSED POWER RESISTOR (PDF, English)

Catalog Pages/Data Sheets:
- 1309350_PASSIVE_COMPONENT (PDF, English)
- Aluminium Housed Power Resistors - Type HS Series (PDF, English)
- 4-1773460-6_RESISTIVE_SOLUTIONS_RAIL (PDF, English)
- 8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_... (PDF, English)

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files: (CAD Format & Compression Information)
- 2D Drawing (DXF, Version V)
- 3D Model (IGES, Version V)
- 3D Model (STEP, Version V)

List all Documents

Additional Information:
- Product Line Information

Related Products:
- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type = Fixed Resistor
- Resistor Type = Power Resistor
- Element = Wirewound

Electrical Characteristics:
- Resistance Selection (Ω) = <1K
- Resistance (Ω) = 24
- Power Rating (W) = 200.00
- Tolerance (%) = 5

Termination Features:
- Termination Type = M6 Threaded Stud

Body Features:
- Mount Style = Chassis Mount
- Package, Component Size = 143 x 73

Configuration Features:
- Number of Terminations = 2
- Number of Resistors = 1

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:
- Temperature Coefficient (ppm/°C) = ±50

Operation/Application:
- Application = High Power

Packaging Features:
- Package Type = Loose Piece - Tray

Other:
- Series = HS
- Brand = CGS

Feedback



© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved