




Our commitment. Your advantage.

- [Products](#) | [Documentation](#) | [Resources](#) | [My Account](#) | [Customer Support](#)

[Home](#) > [Products](#) > [By Type](#) > [Resistors](#) > [Product Feature Selector](#) > Product Details

## ER1647KJL Product Details



### ER1647KJL

(1-1623748-0)

TE Internal Number: 1-1623748-0



### Fixed Resistors

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- Resistor Type = Power Resistor
- Resistance Selection = K ?
- Resistance = 47K ?
- Power Rating = 11.00 W
- Tolerance = 5 %

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

- [Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- [Type ER/ERV Series High Power Resistors](#) (PDF, English)

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Resistor Type = Power Resistor
- [Resistance \(?\)](#) = 47K
- [Element](#) = Wirewound
- [Termination Type](#) = Tinned Copper Leads

#### Electrical Characteristics:

- [Resistance Selection \(?\)](#) = K
- [Power Rating \(W\)](#) = 11.00
- [Tolerance \(%\)](#) = 5
- [Package Type](#) = Loose Piece - Tray

#### Body Related Features:

- [Series](#) = ER
- [Mount Style](#) = Axial Leaded
- [Package, Component Size](#) = 38.1 x 8

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

#### Conditions for Usage:

- [Temperature Coefficient \(ppm/°C\)](#) = ?200

#### Operation/Application:

- [Application](#) = Power

#### Other:

- Brand = CGS

[Provide Website Feedback](#) | [Need Help?](#)