




Our commitment. Your advantage.

- [Products](#) | [Documentation](#) | [Resources](#) | [My Account](#) | [Customer Support](#)


[Home](#) > [Products](#) > [By Type](#) > [Resistors](#) > [Product Feature Selector](#) > Product Details

H85K76FDBER Product Details



H85K76FDBER
(1614085-4)

TE Internal Number: 1614085-4



[Search for Replacement Parts](#)

Fixed Resistors

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Resistor Type = Precision Resistor
- Resistance Selection = K ?
- Resistance = 5.76K ?
- Power Rating = .25 W
- Tolerance = 1 %

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

- [Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [Type HOLCO Series Axial Leaded Precision Resistors](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Resistor Type = Precision Resistor
- [Resistance \(?\)](#) = 5.76K
- [Element](#) = Thin Film
- [Termination Type](#) = Tinned Copper Leads

Electrical Characteristics:

- [Resistance Selection \(?\)](#) = K
- [Power Rating \(W\)](#) = 0.25
- [Tolerance \(%\)](#) = 1
- [Package Type](#) = Bandoliered

Body Related Features:

- [Series](#) = H8
- [Mount Style](#) = Axial Leaded
- [Package, Component Size](#) = 7.2 x 2.5

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- [Temperature Coefficient \(ppm/°C\)](#) = ?25

Operation/Application:

- [Application](#) = Precision

Other:

- [Release Code](#) = B
- Brand = Holsworthy

[Provide Website Feedback](#) | [Need Help?](#)