

Our commitment. Your advantage.

Search

**Live Product Chat** 

Check Pricing & Availability

**Contact Us About This Product** 

<u>Product Feature Selector</u>

Search for Tooling

**Quick Links** 

**Products** 

**Documentation** 

Resources

**My Account** 

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > Product Details

# **SIL12M222J Product Details**



SIL12M222J

(1622810-4)

TE Internal Number: 1622810-4



#### **Fixed Resistors**

<u>Converted to EU RoHS/ELV Compliant</u> (Statement of Compliance)

### **Product Highlights:**

- Resistor Type = General Purpose Resistor
- Resistance Selection = K?
- Resistance = 2.2K ?
- Power Rating = .20 W
- Talamana F 0/
- ▶ Tolerance = 5 %

View all Features



Add to My Part List



Request Sample



Find Similar Products



# Documentation & Additional Information

#### **Product Drawings:**

None Available

### Catalog Pages/Data Sheets:

• General Purpose Resistors Networks - Sil Resistor Ne... (PDF, English)

#### **Product Specifications:**

None Available

# **Application Specifications:**

None Available

#### Instruction Sheets:

None Available

# CAD Files:

None Available

#### **Additional Information:**

Product Line Information

#### **Related Products:**

• <u>Tooling</u>

<u>List all Documents</u>

# **Product Features** (Please use the Product Drawing for all design activity)

# **Product Type Features:**

- Resistor Type = General Purpose Resistor
- Resistance (?) = 2.2K
- Element = Thick Film
- <u>Termination Type</u> = Preformed Leadframe

# **Electrical Characteristics:**

- Resistance Selection (?) = K
- Power Rating (W) = 0.20
- <u>Tolerance (%)</u> = 5
- <u>Package Type</u> = Loose Piece Bag

# **Body Related Features:**

- <u>Series</u> = SIL
- <u>Mount Style</u> = SIL Network
- Package, Component Size = 30.48 x 5.08

# **Configuration Related Features:**

- Number of Terminations = 12
- Number of Resistors = 6

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

# **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?100

# Operation/Application:

Application = Various

# Other:

Brand = Citec