Search

Our commitment. Your advantage.

**Products Documentation** 

Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>PolySwitch Resettable Devices</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# TRF250-183 Product Details



TRF250-183 (RF0768-000) TE Internal Number: RF0768-000

Active


#### **PolySwitch Resettable Devices**

Always EU RoHS/ELV Compliant (Statement of Compliance)

## **Product Highlights:**

- Telecom Application
- Family Name = TRF250
- Through Hole Construction
- IH (Room Temperature) = .183 Amps.
- IT (Room Temperature) = .685 Amps.

View all Features









#### **Documentation & Additional Information**

#### **Product Drawings:**

• TRF250-183 (PDF, English)

# Catalog Pages/Data Sheets:

None Available

#### **Product Specifications:**

None Available

#### **Application Specifications:**

• None Available

#### **Instruction Sheets:**

None Available

#### **CAD Files:**

None Available

## **Additional Information:**

Product Line Information

**Quick Links** 

**Check Pricing & Availability** 

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

#### **Related Products:**

• <u>Tooling</u>

## Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- UL Recognized = File No. E74889
- CSA File No. = 78165C

# **Electrical Characteristics:**

- IH (Room Temperature) (Amps.) = 0.183
- IT (Room Temperature) (Amps.) = 0.685
- Vmax Operating (V) = 100
- Rmin(?) = 0.80
- Rmax(?) = 2.000
- R1 Max [Post Trip] (?) = 3.40
- Vmax Interrupt (V rms) = 250
- UL Rated Voltage (V) = 100

## Termination Related Features:

• Construction = Through Hole

# **Body Related Features:**

Lead Type = Kinked

## **Contact Related Features:**

• Family Name = TRF250

## **Configuration Related Features:**

Coating = Coated

## **Industry Standards:**

**List all Documents** 

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041425

# **Conditions for Usage:**

Operating Temperature (Max.) (?C) = 85

## **Operation/Application:**

Application = Telecom

## **Packaging Related Features:**

Packaging Method = Bulk

## Other:

Brand = Raychem

Provide Website Feedback | Need Help?