

TRF250-180 Product Details

**TRF250-180**

TE Internal Number: E46226-000

 [Active](#)

PolySwitch Resettable Devices

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))**Product Highlights:**

- Telecom Application
- Family Name = TRF250
- Through Hole Construction
- IH (Room Temperature) = .18 Amps.
- IT (Room Temperature) = .65 Amps.

[View all Features](#)

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

 [Add to My Part List](#)  [Request Sample](#)  [Find Similar Products](#)  [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [TRF250-180](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C
- Comment = Designed for equipment needing to meet ITU K.20, K.21, K.45 recommendations.

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.18
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.65
- [Vmax Operating \(V\)](#) = 100
- [Rmin \(?\)](#) = 0.80
- [Rmax \(?\)](#) = 2.200
- [R1 Max \[Post Trip\] \(?\)](#) = 4.00
- [Vmax Interrupt \(V rms\)](#) = 250
- Power Dissipation (Typical) (W) = 1.50
- R (Typical) (?) = 1.50
- UL Rated Voltage (V) = 100

Termination Related Features:

- Construction = Through Hole

Body Related Features:

- Lead Type = Kinked

Contact Related Features:

- Family Name = TRF250

Configuration Related Features:

- Coating = Coated

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Telecom

Packaging Related Features:

- Packaging Method = Bulk, Tape & Reel

Other:

- Brand = Raychem