



What can we help you find?

[Products](#) [Industries](#) [Resources](#) [About TE](#) [My Account](#) [Innovation](#) [Support Center](#)**1206SFS150F/63-2 Product Details**[Share](#)[Print](#)[Email](#)**1206SFS150F/63-2**

TE Internal Number: E77174-000

[Active](#)**Fuses**[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)**Product Highlights:**

- Type = DC Slow Blow Fuse
- Surface Mount Construction
- Form Factor (inches) = 1206
- Form Factor (mm) = 3216
- Rated Current = 1.5 A

[View all Features](#)**Quick Links**

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)**Documentation & Additional Information****Product Drawings:**

- None Available

Catalog Pages/Data Sheets:

- [CP CATALOG 2011-FUSES](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)**Product Features (Please use the Product Drawing for all design activity)****Product Type Features:**

- Family Name = SFS
- UL Listed = File No. E197536

Electrical Characteristics:

- Rated Current (A) = 1.5
- Cold DCR (Nominal) (Ω) = 0.150
- I^2t (A²sec)² (Nominal) (Ω) = 0.23
- Interrupt Voltage, Max. (VDC) = 63
- Interrupt Current, Max. (A) = 50

Termination Features:

- Construction = Surface Mount

Body Features:

- Type = DC Slow Blow Fuse

Configuration Features:

- Form Factor (inches) = 1206
- Form Factor (mm) = 3216

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Operating Temperature (Max.) (°C) = 125

Conditions for Usage:

- Min Clear Time @ 100% Rated Current (Hr) = 4
- Min Clear Time @ 200% Rated Current (Seconds) = 1
- Min Clear Time @ 300% Rated Current (Seconds) = 0.1
- Min Clear Time @ 800% Rated Current (Seconds) = 0.0016 - 0.002

Other:

- Brand = Raychem

Corporate Information[About TE](#)[Investors](#)[News Room](#)[Supplier Portal](#)[Careers](#)[Terms & Conditions](#)**Quick Links**[Check Distributor Inventory](#)[Cross Reference Products](#)[Find Documents & Drawings](#)[Product Compliance Support Center](#)[Site Map](#)**Customer Support**[Email or Chat With Us](#)[Find a Phone Number](#)[Search Knowledge Base](#)[Manage Your Account](#)**Keep Me Informed**

[Privacy Policy](#)

Receive TE News, Events &
Technology Updates

Enter your email address

