



213734-2 Product Details



213734-2

CPC (Circular Plastic) and Circular Metal-Shell Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector Assembly
- Connector Style = Receptacle
- 16 Positions
- 16 Signal Positions
- 0 Power Positions

[View all Features](#)

TE Internal Number: 213734-2

Active

[View 3D PDF](#)

[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Feedback

Documentation & Additional Information

Product Drawings:

- [RECEPTACLE ASSEMBLY, 22-16, STD SEX, CMC](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- [Circular Plastic Connectors \(CPC\)](#) (PDF, English)

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

[List all Documents](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Connector Type = Connector Assembly
- Mount Angle = Straight
- Shell Size = 22
- PCB Mount Retention = Without
- Shell Type = Metal
- Thread Size = 1-3/16-18 UNEF 3B
- Sealed = No

Mechanical Attachment:

- Mount = Panel
- Mating Retention Type = Threaded Coupling

Termination Features:

- Contact Termination Type = Through Hole
- Termination Method = Solder
- Termination End Plating = Tin over Copper

Body Features:

- Mount Style = Flange with Mounting Holes

Contact Features:

- Contact Type = Pin
- Contact Plating, Mating Area, Material = Gold (30)
- Reverse Gender = Standard

Housing Features:

- Connector Style = Receptacle
- Mating Alignment Type = Keyed

Configuration Features:

- Number of Positions = 16
- Number of Signal Positions = 16
- Number of Power Positions = 0
- Environmental Protection = Without
- Reverse Numbering = With

Industry Standards:

- VDE Tested = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Fluid Resistance = None

Conditions for Usage:

- Applies To = Printed Circuit Board

Other:

- Brand = AMP

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

