



# THB Grade IIIB Class X2 Interference Suppression Film Capacitor Radial MKP 305 V<sub>AC</sub> - Across the Line



## FEATURES

- IEC 60384-14: 2013 / AMD1: 2016 grade IIIB: 85 °C, 85 % RH, 1000 h at U<sub>RAC</sub>
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

## APPLICATIONS


For industrial across the line X2 applications.

See also application note: [www.vishay.com/doc?28153](http://www.vishay.com/doc?28153)

## LINKS TO ADDITIONAL RESOURCES




3D Models

| QUICK REFERENCE DATA                            |  |
|---|--|
| Rated capacitance range                         | 1 µF to 20 µF<br>(preferred values according to E12)   |
| Capacitance tolerance                           | ± 20 %; ± 10 %   |
| Climatic testing class according to IEC 60068-1 | 40 / 105 / 56B   |
| Rated AC voltage                                | 305 V <sub>AC</sub> ; 50 Hz to 60 Hz   |
| Permissible DC voltage                          | 630 V <sub>DC</sub> at 105 °C<br>850 V <sub>DC</sub> at 85 °C  |
| Maximum application temperature                 | 105 °C   |
| Reference standards                             | EC 60384-14:2013<br>IEC 60384-14:2013 / AMD1:2016<br>EN 60384-14<br>IEC 60065 requires passive flammability class B: for volume ≥ 1750 mm <sup>3</sup><br>UL 60384-14 (2 <sup>nd</sup> edition)<br>CSA-E60384-1:14 (3 <sup>rd</sup> edition) |
| Dielectric                                      | Polypropylene film   |
| Electrodes                                      | Metallized   |
| Construction                                    | Mono construction<br>   |
| Encapsulation                                   | Plastic case, epoxy resin sealed, flame retardant<br>UL-class 94 V-0   |
| Terminals                                       | Tinned wire  |
| Marking   | C-value; tolerance; rated voltage; sub-class; manufacturer's type designation; code for dielectric material; manufacturer location, year and week; manufacturer's logo or name; safety approvals   |

### Note

- For more detailed data and test requirements, contact [rfi@vishay.com](mailto:rfi@vishay.com)

## DIMENSIONS in millimeters




### Note

- Ø dt ± 10 % of standard diameter specified



## COMPOSITION OF CATALOG NUMBER



## Note

- For detailed tape specifications refer to packaging information [www.vishay.com/doc?28139](http://www.vishay.com/doc?28139)

## SPECIFIC REFERENCE DATA

| DESCRIPTION   | VALUE   |                          |
|---|---|--------------------------|
| Rated AC voltage (U <sub>RAC</sub> )  | 305 V <sub>AC</sub>   |                          |
| Permissible DC voltage (U <sub>RDC</sub> )  | 630 V <sub>DC</sub> at 105 °C<br>850 V <sub>DC</sub> at 85 °C |                          |
| Tangent of loss angle:<br>1 $\mu$ F < C $\leq$ 4.7 $\mu$ F<br>4.7 $\mu$ F < C $\leq$ 12 $\mu$ F<br>C > 12 $\mu$ F                                     | At 1 kHz  | At 10 kHz                |
|   | $\leq 30 \times 10^{-4}$                                      | $\leq 60 \times 10^{-4}$ |
|   | $\leq 50 \times 10^{-4}$                                      | -                        |
|   | $\leq 100 \times 10^{-4}$                                     | -                        |
| Rated voltage pulse slope (du/dt) <sub>R</sub> at 435 V <sub>DC</sub><br>Pitch = 27.5 mm<br>Pitch = 37.5 mm<br>Pitch = 52.5 mm                        | 100 V/ $\mu$ s<br>50 V/ $\mu$ s<br>15 V/ $\mu$ s              |                          |
| RC between leads, for C > 0.33 $\mu$ F at 100 V; 1 min  | > 5000 s  |                          |
| R between leads and case; 100 V; 1 min  | > 30 000 M $\Omega$   |                          |
| Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time $\leq$ 1000 V/s:<br>1 $\mu$ F $\leq$ C $\leq$ 12 $\mu$ F<br>> 12 $\mu$ F | 2200 V; 1 min<br>1800 V; 1 min                                |                          |
| Withstanding (AC) voltage between leads and case  | 2110 V; 1 min   |                          |




## Note

- <sup>(1)</sup> See "Voltage Proof Test for Metalized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)

| ELECTRICAL DATA AND ORDERING INFORMATION |   |  |             |  |                                  |     |                                   |     |
|--|---|--|-------------|--|----------------------------------|-----|-----------------------------------|-----|
| U <sub>RAC</sub><br>(V)                  | CAP.<br>(μF)  | DIMENSIONS <sup>(1)</sup><br>w x h x l<br>(mm) | MASS<br>(g) | CATALOG NUMBER F340X2... AND PACKAGING |                                  |     |                                   |     |
|  |   |  |             | LOOSE IN BOX                           |                                  |     |                                   |     |
|  |   |  |             | SHORT LEADS                            |                                  |     | LONG LEADS                        |     |
|  |   |  |             | l <sub>t</sub> = 3.5 mm ± 0.5 mm       | l <sub>t</sub> = 5.0 mm ± 1.0 mm | SPQ | l <sub>t</sub> = 25.0 mm ± 2.0 mm | SPQ |
| 305                                      | PITCH = 27.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 20 % |  |             |  |                                  |     |                                   |     |
|  | 1.0   | 15.0 x 25.0 x 32.0                             | 14.0        | 51030MKP2T0                            | 51030MKM2T0                      | 95  | 51030MKI2T0                       | 95  |
|  | 1.5   | 15.0 x 25.0 x 32.0                             | 13.1        | 51530MKP2T0                            | 51530MKM2T0                      | 95  | 51530MKI2T0                       | 95  |
|  | 2.2   | 18.0 x 28.0 x 32.0                             | 17.9        | 52230MKP2T0                            | 52230MKM2T0                      | 80  | 52230MKI2T0                       | 80  |
|  | 3.3   | 21.0 x 31.0 x 32.0                             | 23.6        | 53330MKP2T0                            | 53330MKM2T0                      | 65  | 53330MKI2T0                       | 65  |
|  | 4.7   | 22.0 x 38.0 x 32.0                             | 29.1        | 54730MKP2T0                            | 54730MKM2T0                      | 65  | 54730MKI2T0                       | 60  |
|  | PITCH = 37.5 mm ± 0.5 mm; d <sub>t</sub> = 1.0 mm ± 0.1 mm; C-TOL. = ± 20 %   |  |             |  |                                  |     |                                   |     |
|  | 6.8   | 21.5 x 38.5 x 42.0                             | 36.9        | 56830MPP2T0                            | 56830MPM2T0                      | 84  | 56830MPI2T0                       | 84  |
|  | 10  | 30.0 x 45.0 x 42.0                             | 64.9        | 61030MPP2T0                            | 61030MPM2T0                      | 63  | 61030MPI2T0                       | 63  |
|  | PITCH = 52.5 mm ± 0.5 mm; d <sub>t</sub> = 1.2 mm ± 0.12 mm; C-TOL. = ± 20 %  |  |             |  |                                  |     |                                   |     |
|  | 15  | 30.0 x 45.0 x 57.5                             | 85.9        | 61530MYP2T0                            | 61530MYM2T0                      | 45  | 61530MYI2T0                       | 45  |
|  | 20  | 35.0 x 50.0 x 57.5                             | 114.7       | 62030MYP2T0                            | 62030MYM2T0                      | 40  | 62030MYI2T0                       | 40  |
|  | PITCH = 27.5 mm ± 0.4 mm; d <sub>t</sub> = 0.80 mm ± 0.08 mm; C-TOL. = ± 10 % |  |             |  |                                  |     |                                   |     |
|  | 1.0   | 15.0 x 25.0 x 32.0                             | 13.9        | 51030KKP2T0                            | 51030KKM2T0                      | 95  | 51030KKI2T0                       | 95  |
|  | 1.2   | 15.0 x 25.0 x 32.0                             | 13.3        | 51230KKP2T0                            | 51230KKM2T0                      | 95  | 51230KKI2T0                       | 95  |
|  | 1.5   | 15.0 x 25.0 x 32.0                             | 12.9        | 51530KKP2T0                            | 51530KKM2T0                      | 95  | 51530KKI2T0                       | 95  |
|  | 1.8   | 18.0 x 28.0 x 32.0                             | 18.1        | 51830KKP2T0                            | 51830KKM2T0                      | 80  | 51830KKI2T0                       | 80  |
|  | 2.2   | 18.0 x 28.0 x 32.0                             | 17.5        | 52230KKP2T0                            | 52230KKM2T0                      | 80  | 52230KKI2T0                       | 80  |
|  | 2.7   | 21.0 x 31.0 x 32.0                             | 23.9        | 52730KKP2T0                            | 52730KKM2T0                      | 65  | 52730KKI2T0                       | 65  |
|  | 3.3   | 21.0 x 31.0 x 32.0                             | 22.9        | 53330KKP2T0                            | 53330KKM2T0                      | 65  | 53330KKI2T0                       | 65  |
|  | 3.9   | 22.0 x 38.0 x 32.0                             | 29.5        | 53930KKP2T0                            | 53930KKM2T0                      | 65  | 53930KKI2T0                       | 60  |
|  | 4.7   | 22.0 x 38.0 x 32.0                             | 28.4        | 54730KKP2T0                            | 54730KKM2T0                      | 65  | 54730KKI2T0                       | 60  |
|  | PITCH = 37.5 mm ± 0.5 mm; d <sub>t</sub> = 1.0 mm ± 0.1 mm; C-TOL. = ± 10 %   |  |             |  |                                  |     |                                   |     |
|  | 5.6   | 21.5 x 38.5 x 42.0                             | 33.8        | 55630KPP2T0                            | 55630KPM2T0                      | 84  | 55630KPI2T0                       | 84  |
|  | 6.8   | 21.5 x 38.5 x 42.0                             | 31.6        | 56830KPP2T0                            | 56830KPM2T0                      | 84  | 56830KPI2T0                       | 84  |
|  | 8.2   | 30.0 x 45.0 x 42.0                             | 57.4        | 58230KPP2T0                            | 58230KPM2T0                      | 63  | 58230KPI2T0                       | 63  |
|  | 10  | 30.0 x 45.0 x 42.0                             | 53.2        | 61030KPP2T0                            | 61030KPM2T0                      | 63  | 61030KPI2T0                       | 63  |
|  | 12  | 30.0 x 45.0 x 42.0                             | 49.3        | 61230KPP2T0                            | 61230KPM2T0                      | 63  | 61230KPI2T0                       | 63  |
|  | PITCH = 52.5 mm ± 0.5 mm; d <sub>t</sub> = 1.2 mm ± 0.12 mm; C-TOL. = ± 10 %  |  |             |  |                                  |     |                                   |     |
|  | 15  | 30.0 x 45.0 x 57.5                             | 83.9        | 61530KYP2T0                            | 61530KYM2T0                      | 45  | 61530KYI2T0                       | 45  |
|  | 18  | 35.0 x 50.0 x 57.5                             | 116.1       | 61830KYP2T0                            | 61830KYM2T0                      | 40  | 61830KYI2T0                       | 40  |
|  | 20  | 35.0 x 50.0 x 57.5                             | 112.0       | 62030KYP2T0                            | 62030KYM2T0                      | 40  | 62030KYI2T0                       | 40  |

**Notes**

- SPQ = Standard Packing Quantity
- (1) For tolerances see chapter "Dimensions Tolerances"

| APPROVALS   |                     |               |                   |  |
|---|---------------------|---------------|-------------------|--|
| SAFETY APPROVALS X2   | VOLTAGE             | VALUE         | FILE NUMBERS      | LINK   |
| EN 60384-14 (ENEC)<br>(= IEC 60384-14 ed-4 2013)  | 305 V <sub>AC</sub> | 1 μF to 20 μF | 40049214          | <a href="http://www.vishay.com/doc?28258">www.vishay.com/doc?28258</a> |
| UL 60384-14 (2 <sup>nd</sup> edition)   | 305 V <sub>AC</sub> | 1 μF to 20 μF | E354331           | <a href="http://www.vishay.com/doc?28261">www.vishay.com/doc?28261</a> |
| CSA-E60384-1:14 (3 <sup>rd</sup> edition)   | 305 V <sub>AC</sub> | 1 μF to 20 μF | E354331           | <a href="http://www.vishay.com/doc?28261">www.vishay.com/doc?28261</a> |
| CQC   | 305 V <sub>AC</sub> | 1 μF to 20 μF | CQC9001219625 (L) | <a href="http://www.vishay.com/doc?28259">www.vishay.com/doc?28259</a> |
|   |                     |               | CQC9001219626 (F) | <a href="http://www.vishay.com/doc?28260">www.vishay.com/doc?28260</a> |
| CB-test certificate   | 305 V <sub>AC</sub> | 1 μF to 20 μF | DE1-61671/A1      | <a href="http://www.vishay.com/doc?28257">www.vishay.com/doc?28257</a> |
| The ENEC-approval together with the CB-certificate replace all national marks of the following countries (they have already signed the ENEC-agreement): Austria; Belgium; Czech Republic; Denmark; Finland; France; Germany; Greece; Hungary; Ireland; Italy; Luxembourg; Netherlands; Norway; Portugal; Slovenian; Spain; Sweden, Switzerland, and United Kingdom. |                     |               |                   |  |
|      |                     |               |                   |  |

## MOUNTING

### Normal Use

The capacitor unit is designed for mounting on printed-circuit boards. The capacitors packed in bandoleers are designed for mounting in printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information [www.vishay.com/docs?28139](http://www.vishay.com/docs?28139)

### Specific Method of Mounting to Withstand Vibration and Shock

The capacitor unit is designed for mounting on a printed-circuit board. In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board. The capacitor shall be mechanically fixed by the leads and the body clamped.

### Dimensions Tolerances

For the maximum product dimensions for length ( $l_{max.}$ ), width ( $w_{max.}$ ), and height ( $h_{max.}$ ) use the following tolerances:

$$l_{max.} = l + \Delta l, w_{max.} = w + \Delta w, \text{ and } h_{max.} = h + \Delta h$$

- For products with pitch = 27.5 mm,  $\Delta w = \Delta l = \Delta h = 0.7$  mm
- For products with pitch = 37.5 mm,  $\Delta w = \Delta l = \Delta h = 0.7$  mm
- For products with pitch = 52.5 mm,  $\Delta w = \Delta l = \Delta h = 1.0$  mm

For the minimum product dimensions for length ( $l_{min.}$ ), width ( $w_{min.}$ ) and height ( $h_{min.}$ ) following tolerances of the components are valid:

$$l_{min.} = l - \Delta l, w_{min.} = w - \Delta w, \text{ and } h_{min.} = h - \Delta h$$

- For products with pitch = 27.5 mm,  $\Delta w = \Delta l = \Delta h = 1.0$  mm
- For products with pitch = 37.5 mm,  $\Delta w = \Delta l = \Delta h = 1.0$  mm
- For products with pitch = 52.5 mm,  $\Delta w = \Delta l = \Delta h = 1.5$  mm

### Space Requirements for Printed-Circuit Board


For product height with seating plane as given by "IEC 60717" as reference.

The maximum space for length ( $l_{max.}$ ), width ( $w_{max.}$ ), and height ( $h_{max.}$ ) of film capacitors to take in account on the printed-circuit board is shown in the drawings.

- For products with pitch = 27.5 mm,  $\Delta w = \Delta l = \Delta h = 0.7$  mm
- For products with pitch = 37.5 mm,  $\Delta w = \Delta l = \Delta h = 0.7$  mm
- For products with pitch = 52.5 mm,  $\Delta w = \Delta l = \Delta h = 1.0$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.

The maximum length and width of film capacitors is shown in the figure:



## SOLDERING CONDITIONS

For general soldering conditions and wave soldering profile we refer to the document "Soldering Guidelines for Film Capacitors": [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

## STORAGE TEMPERATURE

$T_{stg} = -25\text{ }^{\circ}\text{C}$  to  $+35\text{ }^{\circ}\text{C}$  with RH maximum 75 % without condensation


## RATINGS AND CHARACTERISTICS REFERENCE CONDITIONS

Unless otherwise specified, all electrical values apply to an ambient temperature of  $23\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ , an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50\text{ \%} \pm 2\text{ \%}$ .


For reference testing, a conditioning period shall be applied over 96 hours  $\pm$  4 hours by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.




## CHARACTERISTICS




Capacitance as a function of ambient temperature (typical curve)




Impedance as a function of frequency (typical curve)




Max. RMS current as a function of frequency



Tangent of loss angle as a function of frequency (typical curve)



Max. RMS voltage as a function of frequency



Insulation resistance as a function of ambient temperature (typical curve)

| HEAT CONDUCTIVITY (if applicable) |      |      |                              |
|-----------------------------------|------|------|------------------------------|
| DIMENSION (mm)                    |      |      | HEAT CONDUCTIVITY<br>(mW/°C) |
| w                                 | h    | l    |                              |
| 15.0                              | 25.0 | 32.0 | 33                           |
| 18.0                              | 28.0 | 32.0 | 40                           |
| 21.0                              | 31.0 | 32.0 | 46                           |
| 22.0                              | 38.0 | 32.0 | 55                           |
| 21.5                              | 38.5 | 42.0 | 67                           |
| 30.0                              | 45.0 | 42.0 | 90                           |
| 30.0                              | 45.0 | 57.5 | 113                          |
| 35.0                              | 50.0 | 57.5 | 133                          |

### POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE (if applicable)

The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free air ambient temperature.


The power dissipation can be calculated according type detail specification [www.vishay.com/doc?28147](http://www.vishay.com/doc?28147).

The component temperature rise ( $\Delta T$ ) can be measured or calculated by  $\Delta T = P/G$ :

- $\Delta T = T_{\text{case}} - T_{\text{ambient}}$  = case temperature rise (°C) with a maximum of 15 °C at rated temperature
- P = power dissipation of the component (mW)
- G = heat conductivity of the component (mW/°C)

### MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The case temperature is measured in unloaded ( $T_{\text{amb}}$ ) and loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{\text{amb}}$ .

To avoid radiation or convection, the capacitor should be tested in a wind-free box.

### APPLICATION NOTES

- For X2 electromagnetic interference suppression in standard across the line applications (50 Hz / 60 Hz) with a maximum of 305 V<sub>AC</sub> rated voltage including fluctuation of the mains. It is recommended to use these components in a mains with maximum nominal voltage of 240 V<sub>AC</sub>. Higher continuous applied voltages will shorten the life time
- For series impedance applications we refer to application note [www.vishay.com/doc?28153](http://www.vishay.com/doc?28153)
- To ensure withstanding high humidity requirements in the application the epoxy adhesion at the leads shall not be damaged. Therefore the leads may not be damaged or not be bent before soldering
- For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact: [rfi@vishay.com](mailto:rfi@vishay.com)
- These capacitors are not intended for continuous pulse applications. For these situations capacitors of the AC and pulse program must be used
- The maximum ambient temperature must not exceed 105 °C
- Rated voltage pulse slope:  
if the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 435 V<sub>DC</sub> and divided by the applied voltage

**INSPECTION REQUIREMENTS****General Notes**

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-14 ed-4 (2013) and Specific Reference Data”.

| <b>INSPECTION REQUIREMENTS</b>                      |   |  |
|---|---|--|
| <b>SUB-CLAUSE NUMBER AND TEST</b>                   | <b>CONDITIONS</b>   | <b>PERFORMANCE REQUIREMENTS</b>  |
| <b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b> |   |  |
| 4.1 Dimensions (detail)                             |   | As specified in chapters “General Data” of this specification  |
| Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $C > 1 \mu\text{F}$ at 1 kHz   |  |
| 4.3 Robustness of terminations                      | Tensile: load 10 N; 10 s<br>Bending: load 5 N; 4 x 90°  | No visible damage  |
| 4.4 Resistance to soldering heat                    | No pre-drying<br>Method: 1A<br>Solder bath: 280 °C ± 5 °C<br>Duration: 10 s   |  |
| 4.19 Component solvent resistance                   | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: 5 min ± 0.5 min<br>Recovery time: min. 1 h, max. 2 h   |  |
| 4.4.2 Final measurements                            | Visual examination  | No visible damage<br>Legible marking   |
|   | Capacitance   | $ \Delta C/C  \leq 5 \%$ of the value measured initially   |
|   | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1 \mu\text{F}$<br>Compared to values measured initially |
|   | Insulation resistance   | As specified in section “Insulation Resistance” of this specification  |
| <b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b> |   |  |
| Initial measurements                                | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $C > 1 \mu\text{F}$ at 1 kHz   |  |
| 4.20 Solvent resistance of the marking              | Isopropyl alcohol at room temperature<br>Method: 1<br>Rubbing material: cotton wool<br>Immersion time: 5 min ± 0.5 min  | No visible damage<br>Legible marking   |
| 4.6 Rapid change of temperature                     | $\theta A = -40 \text{ °C}$<br>$\theta B = +105 \text{ °C}$<br>5 cycles<br>Duration $t = 30 \text{ min}$  |  |
| 4.6.1 Inspection                                    | Visual examination  | No visible damage  |
| 4.7 Vibration                                       | Mounting: see section “Mounting” of this specification<br>Procedure B4:<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration 98 m/s <sup>2</sup><br>(whichever is less severe)<br>Total duration 6 h |  |



| INSPECTION REQUIREMENTS   |   |  |
|---|---|--|
| SUB-CLAUSE NUMBER AND TEST  | CONDITIONS  | PERFORMANCE REQUIREMENTS   |
| 4.7.2 Final inspection  | Visual examination  | No visible damage  |
| 4.9 Shock   | Mounting: see section “Mounting” for more information<br>Pulse shape: half sine<br>Acceleration: 490 m/s <sup>2</sup><br>Duration of pulse: 11 ms |  |
| 4.9.2 Final measurements  | Visual examination  | No visible damage  |
|   | Capacitance   | $ \Delta C/C  \leq 5\%$ of the value measured initially  |
|   | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1\ \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1\ \mu\text{F}$<br>Compared to values measured initially |
|   | Insulation resistance   | As specified in section “Insulation Resistance” of this specification  |
| SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B |   |  |
| 4.11 Climatic sequence  |   |  |
| 4.11.1 Initial measurements   | Capacitance<br>Measured in 4.4.2 and 4.9.2  |  |
|   | Tangent of loss angle:<br>measured initially in C1A and C1B   |  |
| 4.11.2 Dry heat   | Temperature: 105 °C   |  |
| 4.11.3 Damp heat cyclic<br>Test Db<br>First cycle                   | Duration: 16 h  |  |
| 4.11.4 Cold   | Temperature: -40 °C   |  |
| 4.11.5 Damp heat cyclic<br>Test Db<br>remaining cycles              | Duration: 2 h   |  |
| 4.11.6 Final measurements   | Visual examination  | No visible damage<br>Legible marking   |
|   | Capacitance   | $ \Delta C/C  \leq 5\%$ of the value measured in 4.11.1.   |
|   | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1\ \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1\ \mu\text{F}$<br>Compared to values measured in 4.11.1 |
|   | Voltage proof<br>1350 V <sub>DC</sub> ; 1 min between terminations  | No permanent breakdown or flash-over   |
|   | Insulation resistance   | $\geq 50\%$ of values specified in section “Insulation Resistance” of this specification   |






| INSPECTION REQUIREMENTS                |   |   |
|--|---|---|
| SUB-CLAUSE NUMBER AND TEST             | CONDITIONS  | PERFORMANCE REQUIREMENTS  |
| 4.12 Damp heat steady state            | 56 days, 40 °C, 90 % to 95 % RH, no load  |   |
| 4.12.1 Initial measurements            | Capacitance<br>Tangent of loss angle at 1 kHz   |   |
| 4.12.3 Final measurements              | Visual examination  | No visible damage<br>Legible marking  |
|  | Capacitance   | $ \Delta C/C  \leq 5\%$ of the value measured in 4.12.1.  |
|  | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1\ \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1\ \mu\text{F}$<br>Compared to values measured in 4.12.1.                 |
|  | Voltage proof<br>1350 V <sub>DC</sub> ; 1 min between terminations  | No permanent breakdown or flash-over  |
|  | Insulation resistance   | $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification  |
| SUB-GROUP C2A                          |   |   |
| 4.12A Damp heat steady state with load | 85 °C, 85 % RH, load: 305 V <sub>AC</sub><br>Duration: 1000 h   |   |
| 4.12.1A Initial measurements           | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1\ \mu\text{F}$ at 10 kHz<br>for $C > 1\ \mu\text{F}$ at 1 kHz |   |
| 4.12.3A Final measurements             | Visual examination  | No visible damage<br>Legible marking  |
|  | Capacitance   | $ \Delta C/C  \leq 10\%$ of the value measured in 4.12.1A.  |
|  | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.0240$ for: $C \leq 1\ \mu\text{F}$ at 10 kHz<br>$> 0.0180$ for: $C > 1\ \mu\text{F}$ at 1 kHz<br>Compared to values measured in 4.12.1A. |
|  | Voltage proof<br>1350 V <sub>DC</sub> ; 1 min between terminations  | No permanent breakdown or flash-over  |
|  | Insulation resistance   | $\geq 50\%$ of values specified in section "Insulation Resistance" of this specification  |



| <b>INSPECTION REQUIREMENTS</b>    |   |  |
|-----------------------------------|---|--|
| <b>SUB-CLAUSE NUMBER AND TEST</b> | <b>CONDITIONS</b>   | <b>PERFORMANCE REQUIREMENTS</b>  |
| <b>SUB-GROUP C3</b>               |   |  |
| 4.13.1 Initial measurements       | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $C > 1 \mu\text{F}$ at 1 kHz   |  |
| 4.13 Impulse voltage              | 3 successive impulses, full wave, peak voltage:<br>X2: 2.5 kV for $C \leq 1 \mu\text{F}$<br>X2: 2.5 kV $\sqrt{C}$ for $C > 1 \mu\text{F}$<br>Max. 24 pulses | No self healing, breakdowns, or flash-over   |
| 4.14 Endurance                    | Duration: 1000 h<br>1.25 x $U_{RAC}$ at 105 °C<br>Once in every hour the voltage is increased to 1000 $V_{RMS}$ for 0.1 s                                   |  |
| 4.14.7 Final measurements         | Visual examination  | No visible damage<br>Legible marking   |
|                                   | Capacitance   | $ \Delta C/C  \leq 10 \%$ compared to values measured in 4.13.1.   |
|                                   | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1 \mu\text{F}$<br>Compared to values measured in 4.13.1 |
|                                   | Voltage proof<br>1350 $V_{DC}$ ; 1 min between terminations<br>2120 $V_{AC}$ ; 1 min between terminations and case  | No permanent breakdown or flash-over   |
|                                   | Insulation resistance   | $\geq 50 \%$ of values specified in section "Insulation Resistance" of this specification  |
| <b>SUB-GROUP C4</b>               |   |  |
| 4.15 Charge and discharge         | 10 000 cycles<br>Charged to 435 $V_{DC}$<br>Discharge resistance:<br>$R = \frac{435 V_{DC}}{1.25 \times C (du/dt)}$   |  |
| 4.15.1 Initial measurements       | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $C > 1 \mu\text{F}$ at 1 kHz   |  |
| 4.15.3 Final measurements         | Capacitance   | $ \Delta C/C  \leq 10 \%$ compared to values measured in 4.15.1.   |
|                                   | Tangent of loss angle   | Increase of $\tan \delta$ :<br>$\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or<br>$\leq 0.005$ for: $C > 1 \mu\text{F}$<br>Compared to values measured in 4.15.1 |
|                                   | Insulation resistance   | $\geq 50 \%$ of values specified in section "Insulation Resistance" of this specification  |

| INSPECTION REQUIREMENTS  |   |   |
|--|---|---|
| SUB-CLAUSE NUMBER AND TEST   | CONDITIONS  | PERFORMANCE REQUIREMENTS  |
| <b>SUB-GROUP C5</b>  |   |   |
| 4.16 Radio frequency characteristic  | Resonance frequency   | $\geq 0.9$ times the value as specified in section "Resonant Frequency" of this specification   |
| <b>SUB-GROUP C6</b>  |   |   |
| 4.17 Passive flammability<br>Class B for volume $> 1750 \text{ mm}^3$<br>Class C for volume $\leq 1750 \text{ mm}^3$ | Bore of gas jet: $\varnothing 0.5 \text{ mm}$<br>Fuel: butane<br>Test duration for actual volume $V$ in $\text{mm}^3$ :<br><br>$V \leq 250$ : 5 s<br>$250 < V \leq 500$ : 10 s<br>$500 < V \leq 1750$ : 20 s<br>$V > 1750$ : 60 s<br><br>One flame application:<br><br> | After removing test flame from capacitor, the capacitor must not continue to burn for more than 30 s for $V \leq 1750 \text{ mm}^3$ and 10 s for $V > 1750 \text{ mm}^3$ . No burning particle must drop from the sample. |
| <b>SUB-GROUP C7</b>  |   |   |
| 4.18 Active flammability   | 20 cycles of 2.5 kV discharges on the test capacitor connected to $U_{\text{RAC}}$  | The cheese cloth around the capacitors shall not burn with a flame.<br>No electrical measurements are required.   |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.