


# Subminiature Transmissive Optical Sensor with Transistor Output



19601



21848

## DESCRIPTION

The TCPT1300X01 is a compact transmissive sensor that includes an infrared emitter and a phototransistor detector, located face-to-face in a surface mount package.

## FEATURES

- Package type: surface mount
- Detector type: phototransistor
- Dimensions (L x W x H in mm): 5.5 x 4 x 4
- AEC-Q101 qualified
- Gap (in mm): 3
- Aperture (in mm): 0.3
- Typical output current under test:  $I_C = 0.6 \text{ mA}$
- Emitter wavelength: 950 nm
- Moisture sensitivity level (MSL): 1
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC

### Note

\*\* Please see document "Vishay Material Category Policy":  
[www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

## APPLICATIONS

- Automotive optical sensors
- Accurate position sensor for encoder
- Detection of motion speed



## PRODUCT SUMMARY

| PART NUMBER | GAP WIDTH (mm) | APERTURE WIDTH (mm) | TYPICAL OUTPUT CURRENT UNDER TEST <sup>(1)</sup> (mA) | DAYLIGHT BLOCKING FILTER INTEGRATED |
|-------------|----------------|---------------------|---|-------------------------------------|
| TCPT1300X01 | 3              | 0.3                 | 0.6   | No                                  |

### Note

- Conditions like in table basic characteristics/coupler

## ORDERING INFORMATION

| ORDERING CODE | PACKAGING     | VOLUME <sup>(1)</sup>        | REMARKS        |
|---------------|---------------|------------------------------|----------------|
| TCPT1300X01   | Tape and reel | MOQ: 2000 pcs, 2000 pcs/reel | Drypack, MSL 1 |

### Note

- MOQ: minimum order quantity



| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |           |               |                    |
|--|--|-----------|---------------|--------------------|
| PARAMETER  | TEST CONDITION   | SYMBOL    | VALUE         | UNIT               |
| <b>COUPLER</b>   |  |           |               |                    |
| Total power dissipation  | $T_{amb} \leq 95\text{ }^{\circ}\text{C}$                      | $P_{tot}$ | 37.5          | mW                 |
| Junction temperature   |  | $T_j$     | 110           | $^{\circ}\text{C}$ |
| Ambient temperature range  |  | $T_{amb}$ | - 40 to + 105 | $^{\circ}\text{C}$ |
| Storage temperature range  |  | $T_{stg}$ | - 40 to + 125 | $^{\circ}\text{C}$ |
| Soldering temperature  | In accordance with fig. 16                                     | $T_{sd}$  | 260           | $^{\circ}\text{C}$ |
| <b>INPUT (EMITTER)</b>   |  |           |               |                    |
| Reverse voltage  |  | $V_R$     | 5             | V                  |
| Forward current  | $T_{amb} \leq 95\text{ }^{\circ}\text{C}$                      | $I_F$     | 25            | mA                 |
| Forward surge current  | $t_p \leq 10\text{ }\mu\text{s}$                               | $I_{FSM}$ | 200           | mA                 |
| Power dissipation  | $T_{amb} \leq 95\text{ }^{\circ}\text{C}$                      | $P_V$     | 37.5          | mW                 |
| <b>OUTPUT (DETECTOR)</b>   |  |           |               |                    |
| Collector emitter voltage  |  | $V_{CEO}$ | 20            | V                  |
| Emitter collector voltage  |  | $V_{ECO}$ | 7             | V                  |
| Collector current  |  | $I_C$     | 20            | mA                 |
| Collector dark current   | $T_{amb} = 85\text{ }^{\circ}\text{C}$ , $V_{CE} = 5\text{ V}$ | $I_{CEO}$ | 3.3           | $\mu\text{A}$      |


**ABSOLUTE MAXIMUM RATINGS**

Fig. 1 - Power Dissipation Limit vs. Ambient Temperature




Fig. 2 - Forward Current Limit vs. Ambient Temperature

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |             |      |      |      |               |
|---|--|-------------|------|------|------|---------------|
| PARAMETER   | TEST CONDITION   | SYMBOL      | MIN. | TYP. | MAX. | UNIT          |
| <b>COUPLER</b>  |  |             |      |      |      |               |
| Collector current   | $V_{CE} = 5\text{ V}$ , $I_F = 15\text{ mA}$   | $I_C$       | 300  | 600  |      | $\mu\text{A}$ |
| Collector emitter saturation voltage  | $I_F = 15\text{ mA}$ , $I_C = 0.05\text{ mA}$  | $V_{CEsat}$ |      |      | 0.4  | V             |
| <b>INPUT (EMITTER)</b>  |  |             |      |      |      |               |
| Forward voltage   | $I_F = 15\text{ mA}$   | $V_F$       | 1    | 1.2  | 1.4  | V             |
| Reverse current   | $V_R = 5\text{ V}$   | $I_R$       |      |      | 10   | $\mu\text{A}$ |
| Junction capacitance  | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$  | $C_j$       |      | 25   |      | pF            |
| <b>OUTPUT (DETECTOR)</b>  |  |             |      |      |      |               |
| Collector emitter voltage $I_C$   | $I_C = 1\text{ mA}$  | $V_{CEO}$   | 20   |      |      | V             |
| Emitter collector voltage   | $I_E = 100\text{ }\mu\text{A}$   | $V_{ECO}$   | 7    |      |      | V             |
| Collector dark current  | $V_{CE} = 25\text{ V}$ , $I_F = 0\text{ A}$ , $E = 0\text{ lx}$                          | $I_{CEO}$   |      | 1    | 100  | nA            |
| <b>SWITCHING CHARACTERISTICS</b>  |  |             |      |      |      |               |
| Rise time   | $I_C = 0.3\text{ mA}$ , $V_{CE} = 5\text{ V}$ , $R_L = 100\text{ }\Omega$ (see figure 3) | $t_r$       |      | 20   | 150  | $\mu\text{s}$ |
| Fall time   | $I_C = 0.3\text{ mA}$ , $V_{CE} = 5\text{ V}$ , $R_L = 100\text{ }\Omega$ (see figure 3) | $t_f$       |      | 30   | 150  | $\mu\text{s}$ |




Fig. 3 - Test Circuit for  $t_r$  and  $t_f$ 


Fig. 4 - Switching Times

## BASIC CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 5 - Forward Current vs. Forward Voltage




Fig. 6 - Forward Voltage vs. Ambient Temperature




Fig. 7 - Collector Current vs. Forward Current




Fig. 10 - Collector Current vs. Ambient Temperature




Fig. 8 - Collector Current vs. Collector Emitter Voltage




Fig. 11 - Collector Dark Current vs. Ambient Temperature




Fig. 9 - Collector Emitter Saturation Voltage vs. Ambient Temperature




Fig. 12 - Relative Collector Current vs. Horizontal Displacement




Fig. 13 - Relative Collector Current vs. Vertical Displacement




Fig. 15 - Application example




Fig. 14 - Rise/Fall Time vs. Collector Current




Fig. 16 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020

### FLOOR LIFE

No time limit.

Moisture sensitivity level (MSL) 1, acc. JEDEC, J-STD-020.

### RELIABILITY TESTS IN REFERENCE TO AEC-Q101 RELEASE


| TEST                          | CONDITION  | DURATION                  | LOT SIZE - REJECTS |
|-------------------------------|--|---------------------------|--------------------|
| High temperature storage      | $T_{stg} (max.) = 100\text{ °C}$   | 1000 h                    | 3 x 50 pcs - 0 pcs |
| Low temperature storage       | $T_{stg} (min.) = -40\text{ °C}$   | 1000 h                    | 3 x 50 pcs - 0 pcs |
| Temperature cycling           | $-40\text{ °C}/+100\text{ °C}$   | 1000 x                    | 3 x 77 pcs - 0 pcs |
| H3TRB                         | 85 °C/85 % RH,<br>emitters: $V_R = 4\text{ V}$ , detectors: $V_{CE0} = 5\text{ V}$   | 1000 h                    | 3 x 77 pcs - 0 pcs |
| Intermittent operational life | Emitters: $I_F = 80\text{ mA DC}$ , detectors: $V_{CE} = 16\text{ V}$ ,<br>duty cycle: 2 min on, 2 min off, $T_{amb} = 25\text{ °C}$ | 1000 h<br>(15 000 cycles) | 3 x 77 pcs - 0 pcs |

### RELIABILITY TESTS IN REFERENCE TO ENHANCED TEMPERATURE RELEASE ACC. AEC-Q101

| TEST                     | CONDITION  | DURATION                  | LOT SIZE - REJECTS |
|--------------------------|--|---------------------------|--------------------|
| High temperature storage | $T_{stg} (max.) = 125\text{ °C}$   | 1000 h                    | 1 x 50 pcs - 0 pcs |
| Temperature cycling      | $-40\text{ °C}/+150\text{ °C}$   | 1000 x                    | 1 x 77 pcs - 0 pcs |
| Power temperature cycle  | $-25\text{ °C}/+85\text{ °C}$ , $I_F = 50\text{ mA}$ , $V_{CE} = 16\text{ V}$ ,<br>2 min. on, 2 min. off | 1000 h<br>(15 000 cycles) | 1 x 77 pcs - 0 pcs |




PACKAGE DIMENSIONS in millimeters



### PACKAGE DIMENSIONS in millimeters

Volume/reel = 2000 pcs



Drawing-No.: 9.800-5092.02-4

Issue: 1; 14.05.07

20601



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.