

Metal Foil Current Sense Resistors, 4-Terminal Low Value (Down to 0.001 Ω)



FEATURES

- 4-terminal design
- Ultra low sensing resistance
- Sulfur resistant according to EIA-977 test method A
- AEC-Q200 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

APPLICATIONS

- Switching power supply
- Voltage regulation module
- DC/DC converter, adaptor, battery pack, charger
- Pad and cell phone
- Power management

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	SIZE	POWER RATING W	TOLERANCE %	RESISTANCE VALUES AVAILABLE m Ω	WEIGHT (typical) g/1000 pieces
WFK0612	0612	1	± 1	0.5, 1, 2, 3, 4, 5, 10	7.40

GLOBAL PART NUMBER INFORMATION

Global Part Numbering Example: WFK0612R0100FE66

W	F	K	0	6	1	2	R	0	1	0	0	F	E	6	6
GLOBAL MODEL (3 digits)			CASE SIZE (EIA) (4 digits)				RESISTANCE VALUE (5 digits) ⁽¹⁾					TOLERANCE CODE (1 digit)	PACKAGING CODE (3 digits)		
WFK			0612				L = m Ω ⁽²⁾ R = decimal 5L000 = 0.005 Ω R0100 = 0.01 Ω					F = ± 1.0 %	E66 = lead (Pb)-free 7" tape/reel		

Notes

- (1) Resistance values are available per E12 and E24 decades; www.vishay.com/doc?28372
- (2) Use "L" for resistance values < 0.01 Ω

TECHNICAL SPECIFICATIONS		
PARAMETER	UNIT	RESISTOR CHARACTERISTICS
		WFK0612
Temperature coefficient	ppm/°C	± 200 for 0.5 mΩ
		± 150 for 1 mΩ to 10 mΩ
Operating temperature range	°C	-55 to +170
Maximum working voltage	V	$(P \times R)^{1/2}$
Maximum element temperature	°C	170

DIMENSIONS in inches (millimeters)





Fig. 1



BOTTOM





Fig. 2

TYPE (INCH SIZE)	RESISTANCE RANGE (mΩ)	DIMENSIONS (in millimeters)					
		L	W	t	A	B	C
WFK0612	0.5 to 10	3.1 ± 0.20	1.6 ± 0.20	0.5 ± 0.20	0.45 ± 0.20	0.45 ± 0.20	2.2 ± 0.20

Note

- 0402 has no marking; 0603, 0805, 1206 marking shows two digits for resistance

DERATING



**PERFORMANCES**

DESCRIPTION	AEC TEST NUMBER	TEST CONDITIONS	LIMIT
High temperature exposure (storage)	3	MIL-STD-202, Method 108, 1000 h at T = 170 °C at 0 % power, measurements at 24 h ± 4 h.	± (1.0 %)
Temperature cycling	4	JESD22 Method JA-104; 1000 cycles (-55 °C to +155 °C), measurement at 24 h ± 4 h after test conclusion. 15 min. dwell time at each temperature extreme. 1 min. maximum transition time.	± (2.0 %)
Moisture resistance	6	MIL-STD-202, Method 106, t = 24 h/cycle. Note: Steps 7a and 7b not required, 0 % power, no polo, 65 °C, measurement at 24 h ± 2 h after test.	± (1.0 %)
Biased humidity	7	MIL-STD-202, Method 103, 1000 h 85 °C/85 % RH. Note: specified conditions: 10 % of operating power. Measurement at 24 h ± 4 h after test.	± (1.0 %)
Operational life	8	MIL-STD-202 Method 108; 1000 h test; Condition D; 1.5 h "ON", 0.5 h "OFF"; terminal temperature +100 °C at rated power. Measurement 24 h ± 4 h after test conclusion.	± (1.0 %)
Resistance to solvents	12	MIL-STD-202 Method 215; Note: add aqueous wash chemical - OKEM clean or equivalent.	Marking remains legible
Mechanical shock	13	MIL-STD-202, Method 213, Condition C	± (1.0 %)
Vibration	14	MIL-STD-202 Method 204; 5 g's for 20 min., 12 cycles each of 3 orientations. Test from 10 Hz to 2000 Hz. Verify transfer load using a laser vibrometer or other adequate measuring device.	± (1.0 %)
Resistance to solder heat	15	MIL-STD-202, Method 210, Condition K	± (1.0 %)
Solderability	18	J-STD-002; Method D; 4 h at +155 °C dry heat; +260 °C lead (Pb)-free; no electrical test; 50 x mag.	> 95 % coverage
Electrical characterization	19	RTC at -55 °C and 170 °C tref. +25 °C	Refer to Technical Specifications table
Flammability	20	UL 94	V-0
Board flex	21	AEC-Q200-005; 2 mm min., 60 s hold time.	± (1.0 %)
Terminal strength (SMD)	22	AEC-Q200-006 force of 1.8 kg for 60 s.	± (1.0 %)
Short time overload		MIL-PRF-55342 paragraph 4.8.6: 5 x rated power for 5 s.	± (1.0 %)
Low temperature storage		MIL-PRF-26 Paragraph 4.7.12	± (1.0 %)

Note

- Full qualification data available upon request at ww2bresistors@vishay.com


TAPE PACKAGING SPECIFICATIONS

MODEL	REEL		
	TAPE WIDTH	DIAMETER	PIECES/REEL
WFK0612	Embossed paper tape	178 mm / 7"	5000

Note

- Embossed carrier tape per EIA (EIAJ)

PAPER TAPE SPECIFICATIONS



TYPE	RESISTANCE RANGE	CARRIER DIMENSIONS (in millimeters)									
		A	B	E	F	W	P0	P1	P2	D0	T
WFK0612	0.5 mΩ to 10 mΩ	2.0 ± 0.05	3.6 ± 0.05	1.75 ± 0.1	3.5 ± 0.05	8.0 ± 0.2	4.0 ± 0.1	2.0 ± 0.1	2.0 ± 0.05	1.55 ± 0.05	0.75 ± 0.1


Notes

- Embossed carrier tape per EIA (EIAJ)
- Additional packaging details at www.vishay.com/doc?20051

STORAGE CONDITIONS

Temperature: 5 °C to 35 °C, humidity: 40 % to 75 %

RECOMMENDED SOLDER PAD LAYOUT



TYPE	PAD LAYOUT DIMENSIONS (in millimeters)				
	a	b	c	d	e
0612 (0.5 mΩ to 10 mΩ)	1.0	3.8	0.80	0.30	0.60

Note

- Recommend to use the steel plate which thickness > 100 μm to avoid the insufficient solder height

SOLDERING RECOMMENDATIONS

- Peak reflow temperatures and durations:
 - IR reflow peak = 260 °C max. for 10 s
 - Wave solder = 260 °C max. for 10 s
- Compatible with lead and lead (Pb)-free solder reflow processes
- Recommended IR reflow profile for surface mount devices: www.vishay.com/doc?31052



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.