

Small Signal Zener Diodes





MARKING (example only)



XYZ = type code (see table below)
bar = pin 1

LINKS TO ADDITIONAL RESOURCES

3D Models | Marking | Parametric Search | Order Samples

FEATURES

- Silicon planar Zener diodes
- Low Zener impedance and low leakage current
- Popular in Asian designs
- Compact surface mount device
- Ideal for automated mounting
- AEC-Q101 qualified available
- ESD capability according to AEC-Q101:
  human body model > 8 kV
  machine model > 800 V
- Base P/N-G3 - Vishay Green, commercial grade
- Base P/N-HG3 - Vishay Green, AEC-Q101 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE GRADE Available

Pb-free

e3

RoHS COMPLIANT

HALOGEN FREE GREEN (5-2008)

PRIMARY CHARACTERISTICS

PARAMETER	VALUE	UNIT
V_Z range nom.	2.0 to 36	V
Test current I_{ZT}	5	mA
V_Z specification	Pulse current	
Circuit configuration	Single	

ORDERING INFORMATION

DEVICE NAME	ORDERING CODE	AEC-Q101 QUALIFIED	TAPED UNITS PER REEL	MINIMUM ORDER QUANTITY
GDZ	GDZ2V0B-G3-08 to GDZ36B-G3-08	No	3000 (8 mm tape on 7" reel)	15 000/box
	GDZ2V0B-HG3_A08 to GDZ36B-HG3_A08	Yes		
	GDZ2V0B-G3-18 to GDZ36B-G3-18	No	10 000 (8 mm tape on 13" reel)	10 000/box
	GDZ2V0B-HG3_A18 to GDZ36B-HG3_A18	Yes		

PACKAGE

PACKAGE NAME	WEIGHT	MOLDING COMPOUND FLAMMABILITY RATING	MOISTURE SENSITIVITY LEVEL	SOLDERING CONDITIONS
SOD-323	4 mg	UL 94 V-0	MSL level 1 (according J-STD-020)	260 °C/10 s at terminals

ABSOLUTE MAXIMUM RATINGS (T_{amb} = 25 °C, unless otherwise specified)

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Power dissipation		P_{tot}	200	mW
Thermal resistance junction to lead		R_{thJL}	625	K/W
Junction temperature		T_j	150	°C
Storage temperature range		T_{stg}	-55 to +150	°C
Operating temperature range		T_{op}	-55 to +150	°C

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

ELECTRICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)									
PART NUMBER	**MARKING CODE**	**ZENER VOLTAGE RANGE**		**TEST CURRENT**		**REVERSE CURRENT**		**DYNAMIC RESISTANCE**	
		V_Z at I_{ZT1}		**I_{ZT1}**	**I_{ZT2}**	**I_R at V_R**		**Z_Z at I_{ZT1}**	**Z_{ZK} at I_{ZT2}**
		V		**mA**		**µA**	**V**	**Ω**	
		MIN.	**max.**			**max.**		**max.**	**max.**
GDZ2V0B-G	V1	2.02	2.2	5	0.5	120	0.5	100	1000
GDZ2V2B-G	V2	2.22	2.41	5	0.5	120	0.7	100	1000
GDZ2V4B-G	V3	2.43	2.63	5	0.5	120	1	100	1000
GDZ2V7B-G	V4	2.69	2.91	5	0.5	100	1	110	1000
GDZ3V0B-G	V5	3.01	3.22	5	0.5	50	1	120	1000
GDZ3V3B-G	V6	3.32	3.53	5	0.5	20	1	120	1000
GDZ3V6B-G	V7	3.6	3.845	5	1	10	1	100	1000
GDZ3V9B-G	V8	3.89	4.16	5	1	5	1	100	1000
GDZ4V3B-G	V9	4.17	4.43	5	1	5	1	100	1000
GDZ4V7B-G	V0	4.55	4.75	5	0.5	2	1	100	800
GDZ5V1B-G	VA	4.98	5.2	5	0.5	2	1	80	500
GDZ5V6B-G	VB	5.49	5.73	5	0.5	1	2.5	60	200
GDZ6V2B-G	VC	6.06	6.33	5	0.5	1	3	60	100
GDZ6V8B-G	VD	6.65	6.93	5	0.5	0.5	3.5	40	60
GDZ7V5B-G	VE	7.28	7.6	5	0.5	0.5	4	30	60
GDZ8V2B-G	VF	8.02	8.36	5	0.5	0.5	5	30	60
GDZ9V1B-G	VG	8.85	9.23	5	0.5	0.5	6	30	60
GDZ10B-G	VH	9.77	10.21	5	0.5	0.1	7	30	60
GDZ11B-G	VI	10.76	11.22	5	0.5	0.1	8	30	60
GDZ12B-G	VJ	11.74	12.24	5	0.5	0.1	9	30	80
GDZ13B-G	VK	12.91	13.49	5	0.5	0.1	10	37	80
GDZ15B-G	VL	14.34	14.98	5	0.5	0.1	11	42	80
GDZ16B-G	VM	15.85	16.51	5	0.5	0.1	12	50	80
GDZ18B-G	VN	17.56	18.35	5	0.5	0.1	13	65	80
GDZ20B-G	VO	19.52	20.39	5	0.5	0.1	15	85	100
GDZ22B-G	VP	21.54	22.47	5	0.5	0.1	17	100	100
GDZ24B-G	VR	23.72	24.78	5	0.5	0.1	19	120	120
GDZ27B-G	VS	26.19	27.53	5	0.5	0.1	21	150	150
GDZ30B-G	VT	29.19	30.69	5	0.5	0.1	23	200	200
GDZ33B-G	VU	32.15	33.79	5	0.5	0.1	25	250	250
GDZ36B-G	VV	35.07	36.87	5	0.5	0.1	27	300	300

Notes

- The Zener voltage V_Z is measured 40 ms after power is supplied
- The operating resistance (Z_Z, Z_{ZK}) are measured by superimposing a 1 kHz alternating current on the regulated current (I_Z)

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

TYPICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)





Fig. 1 - Zener Voltage Temperature Coefficient vs. Zener Voltage

PACKAGE DIMENSIONS in millimeters (inches): SOD-323



Footprint recommendation:

Document no.: S8-V-3910.02-001 (4)
Created - Date: 24.August.2004
Rev. 6 - Date: 23.Sept.2016
17443

For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2026 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000