

# 1N5518B-1 thru 1N5546B-1



## Low Noise Zener Diode Series

Rev. V4

### Features

- Available in JAN, JANTX and JANTXV PER MIL-PRF-19500/437
- Low Reverse Leakage Characteristics
- Low Noise Characteristics
- Double Plug Construction DO-35 Axial Lead Package
- Metallurgically Bonded
- Also available in DO-213AA MELF style package.



### Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

JEDEC TYPE Number (Note 1)	Normal Zener Voltage $V_z$ @ IZT	Zener Test Current IZT	Maximum Zener Impedance B-C-D Suffix ZZT @ IZT	Maximum Reverse Leakage Current			B-C-D Suffix Maximum DC Zener Current IZM	B-C-D Suffix Maximum Noise Density @ IZ=250 mA ND	Regulation Factor $\Delta V_Z$ (Note 2)	Low VZ Current IZL
				IR	VR = Volts					
	Volts	mA	Ohms	m Adc	NON & A- Suffix	B-C-D-Suffix	mAdc	mV / $\sqrt{\text{Hz}}$	Volts	mAdc
1N5518B	3.3	20	26	5.0	0.90	1.0	115	0.5	0.90	2.0
1N5519B	3.6	20	24	3.0	0.90	1.0	105	0.5	0.90	2.0
1N5520B	3.9	20	22	1.0	0.90	1.0	98	0.5	0.85	2.0
1N5521B	4.3	20	18	3.0	1.0	1.5	88	0.5	0.75	2.0
1N5522B	4.7	10	22	2.0	1.5	2.0	81	0.5	0.60	1.0
1N5523B	5.1	5.0	26	2.0	2.0	2.5	75	0.5	0.65	0.25
1N5524B	5.6	3.0	30	2.0	3.0	3.5	68	1.0	0.30	0.25
1N5525B	6.2	1.0	30	1.0	4.5	5.0	61	1.0	0.20	0.01
1N5526B	6.8	1.0	30	1.0	5.5	6.2	56	1.0	0.10	0.01
1N5527B	7.5	1.0	35	0.5	6.0	6.8	51	2.0	0.05	0.01
1N5528B	8.2	1.0	40	0.5	6.5	7.5	46	4.0	0.05	0.01
1N5529B	9.1	1.0	45	0.1	7.0	8.2	42	4.0	0.05	0.01
1N5530B	10.0	1.0	60	0.05	8.0	9.1	38	4.0	0.10	0.01
1N5531B	11.0	1.0	80	0.05	9.0	9.9	35	5.0	0.20	0.01
1N5532B	12.0	1.0	90	0.05	9.5	0.8	32	10	0.20	0.01
1N5533B	13.0	1.0	90	0.01	10.5	11.7	29	15	0.20	0.01
1N5534B	14.0	1.0	100	0.01	11.5	12.6	27	20	0.20	0.01
1N5535B	15.0	1.0	100	0.01	12.5	13.5	25	20	0.20	0.01

(Continued next page)

# 1N5518B-1 thru 1N5546B-1



## Low Noise Zener Diode Series

Rev. V4

### Electrical Specifications: $T_A = +25^\circ\text{C}$ (unless otherwise specified)

JEDEC TYPE Number (Note1)	Normal Zener Voltage $V_Z @ I_{ZT}$	Zener Test Current $I_{ZT}$	Maximum Zener Impedance B-C-D Suffix $Z_{ZT} @ I_{ZT}$	Maximum Reverse Leakage Current			B-C-D Suffix Maximum DC Zener Current $I_{ZM}$	B-C-D Suffix Maximum Noise Density $@ I_Z=250 \text{ mA}$ ND	Regulation Factor $\Delta V_Z$ (Note 2)	Low $V_Z$ Current $I_{ZL}$
				IR	VR = Volts					
					m Adc	NON & A- Suffix				
Volts	mA	Ohms	m Adc			mAdc	mV / $\sqrt{\text{Hz}}$	Volts	mAdc	
1N5536B	16.0	1.0	100	0.01	13.0	14.4	24	20	0.20	0.01
1N5537B	17.0	1.0	100	0.01	14.0	15.3	22	20	0.20	0.01
1N5538B	18.0	1.0	100	0.01	15.0	16.2	21	20	0.20	0.01
1N5539B	19.0	1.0	100	0.01	16.0	17.1	20	20	0.20	0.01
1N5540B	20.0	1.0	100	0.01	17.0	18.0	19	20	0.20	0.01
1N5541B	22.0	1.0	100	0.01	18.0	19.8	17	20	0.25	0.01
1N5542B	24.0	1.0	100	0.01	20.0	21.6	16	20	0.30	0.01
1N5543B	25.0	1.0	100	0.01	21.0	22.4	15	20	0.35	0.01
1N5544B	28.0	1.0	100	0.01	23.0	25.2	14	20	0.40	0.01
1N5545B	30.0	1.0	100	0.01	24.0	27.0	13	20	0.45	0.01
1N5546B	33.0	1.0	100	0.01	28.0	29.7	12	20	0.50	0.01

1. No Suffix type numbers are +20% with guaranteed limits for only  $V_Z$ ,  $I_R$ , and  $V_F$ . Units with "A" suffix are +10% with guaranteed limits for  $V_Z$ ,  $I_R$ , and  $V_F$ . Units with guaranteed limits for all six parameters are indicated by a "B" suffix for +5.0% units, "C" suffix for +2.0% and "D" suffix for +1.0%.
2. Delta  $V_Z$  is the maximum difference between  $V_Z @ I_{ZT}$  and  $V_Z @ I_{ZL}$  measured with the device junction in thermal equilibrium.

### Absolute Maximum Ratings


Parameter	Absolute Maximum
Steady State Power Dissipation	500 mW @ +50°C
Forward Voltage	1.1 V @ 200 mA
DC Power Derating	4 mW / °C above +50°C
Operating & Storage Temperature	-65°C to +175°C

# 1N5518B-1 thru 1N5546B-1

## Low Noise Zener Diode Series

Rev. V4

### Outline Drawing (DO-35)



LTR	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
BD	.055	.090	1.40	2.29	3
BL	.120	.200	3.05	5.08	3
LD	.018	.022	0.46	0.56	
LL	1.000	1.500	25.40	38.10	
LU		.050		1.27	4

#### NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Package contour optional within dimension BD and length dimension BL. Heat slugs, if any, shall be included within this cylinder but shall not be subject to minimum limit of dimension BD. The dimension BL shall include the entire body including slugs.
3. Within this zone lead, diameter may vary to allow for lead finishes and irregularities other than heat slugs.
4. In accordance with ASME Y14.5M, diameters are equivalent to  $\phi x$  symbology.

FIGURE 1. Physical dimensions for axial leaded DO-204AH package.


# 1N5518B-1 thru 1N5546B-1



## Low Noise Zener Diode Series


Rev. V4

### Graphs



- NOTES:
- All devices are capable of operating at  $\leq T_j$  specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum  $T_j$  allowed.
  - Derate design curve constrained by the maximum junction temperature ( $T_j \leq 175^\circ\text{C}$ ) and power rating specified. (See 1.3 herein.)
  - Derate design curve chosen at  $T_j \leq 150^\circ\text{C}$ , where the maximum temperature of electrical test is performed.
  - Derate design curve chosen at  $T_j \leq 125^\circ\text{C}$ , and  $110^\circ\text{C}$  to show power rating where most users want to limit  $T_j$  in their application.


FIGURE 4. Temperature-power derating curve ( $T_j$ ) for DO-204AH



NOTE: Thermal resistance =  $300^\circ\text{C/W}$ . Maximum power rating = 400 mW at  $T_A = 55^\circ\text{C}$ .


FIGURE 7. Thermal impedance (DO-204AH and DO-213AA) PCB mount.

### Thermal Impedance DO-204AH



NOTE: Thermal resistance =  $250^\circ\text{C/W}$ . Maximum power rating = 500 mW at  $T_j = 50^\circ\text{C}$ .

FIGURE 8. Thermal impedance (DO-204AH).



- NOTES:
- Input voltage and lead resistance should be high so that zener can be driven from a constant current source.
  - Input impedance of band pass filter should be high compared with the dynamic impedance of the diode under test.
  - Filter bandwidth characteristics shall be as follows:
    - $f_0 = 2,000\text{ Hz}$
    - Shape factor,  $-40\text{ db to }-3\text{ db}$ , approximately 2
    - Passband at the  $-3\text{ db}$  is  $1,000\text{ Hz } \pm 50\text{ Hz to } 3,000\text{ Hz } \pm 150\text{ Hz}$
    - Passband at the  $-40\text{ db}$  is  $500\text{ Hz } \pm 50\text{ Hz to } 6,000\text{ Hz } \pm 600\text{ Hz}$

FIGURE 10. Test circuit for determination of noise density.

### VPT COMPONENTS. ALL RIGHTS RESERVED.

Information in this document is provided in connection with VPT Components products. These materials are provided by VPT Components as a service to its customers and may be used for informational purposes only. Except as provided in VPT Components Terms and Conditions of Sale for such products or in any separate agreement related to this document, VPT Components assumes no liability whatsoever. VPT Components assumes no responsibility for errors or omissions in these materials. VPT Components may make changes to specifications and product descriptions at any time, without notice. VPT Components makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF VPT COMPONENTS PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. VPT COMPONENTS FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. VPT COMPONENTS SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

VPT Components products are not intended for use in medical, lifesaving or life sustaining applications. VPT Components customers using or selling VPT Components products for use in such applications do so at their own risk and agree to fully indemnify VPT Components for any damages resulting from such improper use or sale.