

Color: light gray

Technical data

Rated current	10 A
---------------	------

Connection data

Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	12 mm / 0.472 inches
Depth	74.3 mm / 2.925 inches

Mechanical Data

Pluggable connector	pluggable
---------------------	-----------

Material Data

Color	light gray
Fire load	0.204 MJ
Weight	11.2 g

Environmental requirements

Ambient temperature (operation)	0 ... +55 °C
Surrounding air temperature (storage)	-25 ... +85 °C
Protection type	IP20

Commercial data

Product Group	15 (Remote I/O)
eCl@ss 10.0	27-24-26-92
eCl@ss 9.0	27-24-26-92
ETIM 8.0	EC002584
ETIM 7.0	EC002584
PU (SPU)	25 (1) pcs
Packaging type	Box
Country of origin	CN
GTIN	4050821043928
Customs tariff number	85366990990

Approvals and certificates

General approvals



Approval	Standard	Certificate name
UL Underwriters Laboratories Inc.	UL 1059	E45172

Approvals for marine applications



Approval	Standard	Certificate name
ABS American Bureau of Ship- ping	-	22-2219060
BSH Bundesamt fuer See- schiffahrt und Hydrogra- phie	-	1104
BV Bureau Veritas S.A.	-	30389/B1 BV
DNV DNV Germany GmbH	DNV-CG-0339, Aug.2021	TAA0000194
KR Korean Register of Ship- ping	-	KR HMB05880-AC001
LR Lloyds Register EMEA	-	LR22180952TA
PRS Polski Rejestr Statków	-	TE/2236/880590/19
RINA RINA Germany GmbH	-	ELE343521XG001

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 753-110



Documentation

Manual			
System Manual WAGO I/O System 750 / 753	V 3.1.0 11.05.2022	pdf 8495.90 KB	↓

Bid Text			
753-110	09.01.2019	docx 13.23 KB	↓
753-110	19.02.2019	xml 2.99 KB	↓

CAD/CAE-Data

CAD data
2D/3D Models 753-110

CAE data
EPLAN Data Portal 753-110
WSCAD Universe 753-110
ZUKEN Portal 753-110