

## Updated certificates

Dear Madam or Sir,

The IECEx - Certificate of Conformity (CoC) and the EU Type Examination Certificate for the single level terminal blocks ZDU 4 and ZPE 4 for use in Zone 1 in hazardous areas have been updated.

The ATEX and IECEx certificates are referring to the following standards:

- IEC 60079-0: 2017 Edition: 7.0 Explosive atmospheres - Part 0: Equipment – General requirements)
- IEC 60079-7:2017 Edition 5.1 (Explosive atmospheres - Part 7: Equipment protection by increased safety "eb")

### 1. Initial situation

The ZDU 4 and ZPE 4 are terminal blocks versions with 2 conductor connections on 1 level. The IECEx - Certificate of Conformity (CoC) no longer correspond to the current standard.

### 2. Technical change

No  
The new certification numbers and markings have been modified on the product.

### 3. Reason for change

Ex approvals have been adapted to the current standard status.

### 4. Availability

The ZDU 4 and ZPE 4 product versions are available from June 2020.

### 5. Affected parts

The following parts are affected:

- 1632050000 ZDU 4
- 1632060000 ZDU 4 BL
- 1683620000 ZDU 4 BR
- 1683590000 ZDU 4 GE
- 1683630000 ZDU 4 GR
- 1636830000 ZDU 4 OR
- 1683580000 ZDU 4 RT
- 1683650000 ZDU 4 SW
- 1683640000 ZDU 4 WS
- 1632080000 ZPE 4

## Data

### 1. Technical data

**Current:**

	ZDU 4 and all colour versions	ZPE 4
Product	and all colour versions	
Part Number	1632050000	1632080000
IECEX Certificate of Conformity	IECEXULD05.0009U	
EC type Examination certificate	KEMA97ATEX2521U	
Rated Voltage	550 V	-
Rated Current	28 A	-
Operating temperature range	-50°C...+100°C	

**New:**

	ZDU 4 and all colour versions	ZPE 4
Product	and all colour versions	
Part Number	1632050000	1632080000
IECEX Certificate of Conformity	IECEX ULD 15.0008 U	
EC type Examination certificate	DEMKO 15 ATEX 1467U	
Rated Voltage	550 V	-
Rated Current	28 A	-
Operating temperature range	-60°C...+110°C	

### 2. Documents in the online catalogue

- a. IECEX Certificate of Conformity
- b. EU-Type Examination Certificate
- c. NTI: User instruction; cross connection cases and safety instructions
- d. Attestation of Conformity

Downloads	
Approval/Certificate/Document of Conformity	<a href="#">Attestation of Conformity</a> <a href="#">IECEX Certificate</a> <a href="#">ATEX Certificate</a> <a href="#">CB Test Certificate</a> <a href="#">CB Certificate</a> <a href="#">EAC certificate</a> <a href="#">DNVGL certificate</a> <a href="#">DNVGL certificate</a> <a href="#">INMETRO certificate</a> <a href="#">Lloyds Register Certificate</a> <a href="#">EAC EX Certificate</a> <a href="#">CCC Ex Certificate</a> <a href="#">ATEX Certificate</a> <a href="#">Declaration of Conformity</a> <a href="#">Declaration of Conformity</a>
Engineering Data	<a href="#">STEP</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3,S</a>
CADENAS eCATALOG	<a href="#">Cax data</a>
Product Change Notification	<a href="#">PCN - EN</a> <a href="#">PCN - DE</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a> <a href="#">NTI ZDU/ZPE 4</a>

### 3. Rating data IECEX/ATEX

The rating voltage and rated current is documented in NTI on page 2, subject Technical data according to IEC/EN 60079-7 (increased safety "eb"). In the past, the rated data were specified in the certificate.

	ZDU 4	ZPE 4
Rated voltage	550 V	-
Rated current	28 A / ΔT 40 K	-
Rated current with ZQV...	28 A / ΔT 40 K	-

For further questions please contact your sales office directly. All contacts for sales representatives are available here: [www.weidmueller.com/contact](http://www.weidmueller.com/contact)

Best regards

Product Management

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26, 32758 Detmold

**Weidmüller** – Your partner in Industrial Connectivity  
We look forward to sharing ideas with you – **Let's connect.**