

H0,75/14 W BD



General ordering data

Type	H0,75/14 W BD
Order No.	9004290000
Version	Wire end ferrule, insulated, 10 mm, 8 mm, White
GTIN (EAN)	4008190006778
Qty.	500 pc(s).
Packaging	Reel packaged

Dimensions and weights

Length	14 mm
Length (inches)	0.551 inch
Net weight	0.092 g

Technical data

Version	insulated
---------	-----------

Wire-end ferrules

Collar diameter (D2)	2.8 mm
Colour code	Weidmüller
Conductor cross-section	0.75 mm ²
Contact surface diameter (D1)	1.2 mm
Contact surface length (L2)	8 mm
L1 in mm	14 mm

Metal sleeve thickness (S1)	0.15 mm
Plastic collar thickness (S2)	0.25 mm
Stripping length	10 mm
Wire connection cross section AWG, max.	AWG 18

Downloads

Engineering data	<u>EPLAN, WSCAD, Zuken E3.S</u>
------------------	---

Classifications

ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005
ETIM 6.0	EC000005
UNSPSC	31-16-31-02
eClass 5.1	27-40-02-01
eClass 6.2	27-40-02-01
eClass 7.1	27-40-02-01
eClass 8.1	27-40-02-01
eClass 9.0	27-40-02-01
eClass 9.1	27-40-02-01

Approvals

Approvals



ROHS Conform

UL File Number Search [E354986](#)

Related products:



Order No.: 9004300000
Type: H0,75/14D GR BD
Description of article: Linked wire-end
ferrules, grey

Version:
Wire end ferrule,
insulated, 10 mm, 8
mm, Grey

PDF data sheet
[Add to Inquiry List](#)

Order No.: 9004310000
Type: H0,75/14T HBL BD
Description of article: Wire-end ferrule

Version:
Wire end ferrule,
insulated, 10 mm, 8

mm, Light Blue



[PDF data sheet](#)

[Add to Inquiry List](#)