

IE-USB-A-A-1.0M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



Assembled IE cables

General ordering data

Version	USB cable, USB A, USB A, PVC, 1 m
Order No.	1993550010
Type	IE-USB-A-A-1.0M
GTIN (EAN)	4050118378559
Qty.	1 pc(s).

Creation date July 15, 2021 3:20:10 PM CEST

Catalogue status 02.07.2021 / We reserve the right to make technical changes.

IE-USB-A-A-1.0M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Length	1 m	Length (inches)	39.37 inch
Net weight	38.4 g		

Temperatures

Operating temperature	-15 °C...80 °C
-----------------------	----------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical specifications for cable

Sheathing colour	black
------------------	-------

General technical data

Contact surface	Gold over nickel
-----------------	------------------

Cable structure

Cross-section	2*AWG28 + 2*AWG24	Material sheath	PVC
Sheath diameter	4.5 mm	Sheath diameter, max.	4.7 mm
Sheath diameter, min.	4.3 mm	Sheathing colour	black

Plug, left

Connector left	USB A	Contact surface, plug, left	Gold over nickel
----------------	-------	-----------------------------	------------------

Plug, right

Connector right	USB A	Contact surface	Gold over nickel
-----------------	-------	-----------------	------------------

plug

Connector left	USB A	Connector right	USB A
----------------	-------	-----------------	-------

Classifications

ETIM 6.0	EC000830	ETIM 7.0	EC003249
ETIM 8.0	EC003249	ECLASS 9.0	27-06-20-11
ECLASS 9.1	27-06-90-90	ECLASS 10.0	27-06-01-06
ECLASS 11.0	27-06-01-06		

Approvals

ROHS	Conform
------	---------

IE-USB-A-A-1.0M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN PI PROFINET CABLING EN PI PROFINET CABLING EN
