

PAC-S1200-HE20-V1-2M**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a cross-section of 0.14 mm² or 0.25 mm².
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

General ordering data

Version	Pre-assembled cable, PAC, Cable LiYY, 0.25 mm ²
Order No.	1329 120020
Type	PAC-S1200-HE20-V1-2M
GTIN (EAN)	4032248196753
Qty.	1 pc(s).
Available until	2014-05-20

PAC-S1200-HE20-V1-2M

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	282 g
------------	-------

General Data

Cable	Cable LiYY	Cable length	2 m
Connector PLC side	4 x SIEMENS S7 1200 6ES7292-1AG30-OXA0 7P	Interface connector	HE10 20P
Material	PVC	Number of poles, min.	20-pole
Outer diameter	10 ± 1 mm	Suitable for	Digital signals
Wire cross-section	0.25 mm ²		

Classifications

ETIM 6.0	EC000237	ETIM 7.0	EC000237
ETIM 8.0	EC000237	ECLASS 9.0	27-24-22-20
ECLASS 9.1	27-24-22-20	ECLASS 10.0	27-24-22-20
ECLASS 11.0	27-24-22-20		

Approvals

ROHS	Conform
------	---------

Downloads

Catalogues	Catalogues in PDF-format
------------	--