

**QL 2 SAKG40/35****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image** Similar to illustration

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                                                                                                                   |
|------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), when screwed in, grey, 232 A, Number of poles: 2, Pitch in mm (P): 40.00, Insulated: No, Width: 71 mm |
| Order No.  | <a href="#">0211400000</a>                                                                                                        |
| Type       | QL 2 SAKG40/35                                                                                                                    |
| GTIN (EAN) | 4008190004941                                                                                                                     |
| Qty.       | 5 ST                                                                                                                              |

## QL 2 SAKG40/35

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Dimensions and weights

|            |        |                 |             |
|------------|--------|-----------------|-------------|
| Depth      | 5 mm   | Depth (inches)  | 0.1968 inch |
| Height     | 25 mm  | Height (inches) | 0.9842 inch |
| Width      | 71 mm  | Width (inches)  | 2.7953 inch |
| Net weight | 66.2 g |                 |             |

## Temperatures

|                     |                |                     |               |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

## Environmental Product Compliance

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status               | Compliant with exemption             |
| RoHS Exemption (if applicable/known) | 6c                                   |
| REACH SVHC                           | Lead 7439-92-1                       |
| SCIP                                 | 86596b21-b817-43a9-8e4c-ac00e41b9a24 |

## Material data

|          |      |        |      |
|----------|------|--------|------|
| Material | CuSn | Colour | grey |
|----------|------|--------|------|

## System specifications

|         |                 |
|---------|-----------------|
| Version | Cross-connector |
|---------|-----------------|

## Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Type of fixing           | when screwed in | Installation advice | Direct mounting |
| Explosion-tested version | No              | Type of mounting    | when screwed in |

## Cross-connector

|                                     |       |                           |                 |
|-------------------------------------|-------|---------------------------|-----------------|
| Number of cross-connected terminals | 2     | Type                      | Cross-connector |
| Rated current, 2-pole               | 232 A | Rated current, multi-pole | 232 A           |

## Dimensions

|                 |          |
|-----------------|----------|
| Pitch in mm (P) | 40.00 mm |
|-----------------|----------|

## General

|                 |   |                     |                 |
|-----------------|---|---------------------|-----------------|
| Number of poles | 2 | Installation advice | Direct mounting |
|-----------------|---|---------------------|-----------------|

## Rating data

|               |       |
|---------------|-------|
| Rated current | 232 A |
|---------------|-------|

## Classifications

|          |          |          |          |
|----------|----------|----------|----------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |

## Technical data

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |