



General ordering data

| | |
|------------------|--|
| Order No. | 1019700000 |
| Part designation | WPE 120/150 |
| Version | Earth terminal, 120 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| EAN | 4008190495671 |
| Qty. | 10 pc(s). |

Product notes

| | |
|----------------------|---|
| Note, technical data | For 50 - 150 mm ² , the TS 35x15 (copper, 2.3mm thick) rail should be used. |
| Product description | Direct mounting is possible thanks to the elongated holes on the underside of the terminal. Terminal blocks can be screwed directly to mounting plates with a pitch of 25 mm. |
| Note, accessories | Rail support for insulated installation of terminal rail "SH 2" order no. 0494920000 (10 pcs) |

PT OKIECEEx/ATEX rating data

| | |
|--------------------------------------|---|
| EU-type examination certificate | KEMA98ATEX1686U |
| Download, German | KEMA98ATEX1686U_d.pdf |
| Download English | KEMA98ATEX1686U_e.pdf |
| ATEX conductor cross-section | 120 mm ² |
| Voltage when using cross-connections | CrossConnectionGuide.pdf |
| Operating temperature range | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity |
| Marking EN 60079-7 | Ex e II |
| Marking ATEX Directive 94/9/EC | Ex II 2 G D |

Additional technical data

| | |
|---------------------------------|--------------|
| Colour of insulating material | green/yellow |
| Connection direction | on side |
| End plate required | No |
| Explosion-tested version "Ex e" | Yes |
| Installation advice | TS 35 |

Additional technical data

| | |
|--|-------------------|
| Insulating material | Wemid |
| Levels cross-connected internally | No |
| No. of identical terminals | 1 |
| No. of levels | 1 |
| No. of terminal strips per level | 2 |
| Open sides | closed |
| Operating temperature range | - 50 °C, + 120 °C |
| Product family | W-Series |
| Type of connection | Screwed |
| Type of mounting | Screwed |
| UL 94 flammability rating of insulation material | V-0 |
| Version | PE terminal |

CSA rating data

| | |
|--------------------------|-----------|
| Min. cross-section (CSA) | AWG 2 |
| Max. cross-section (CSA) | kcmil 250 |

Conductors for clamping (rated connection)

| | |
|---|-----------------------|
| Clamping range, min. | 33.62 mm ² |
| Clamping range, max. | 150 mm ² |
| Type of connection | Screw connection |
| 2nd type of connection | screwed |
| Connection direction | on side |
| No. of connections | 2 |
| Stripping length | 35 mm |
| Clamping screw | M 10 |
| Blade size | S6 (DIN 6911) |
| Tightening torque range | 10...20 Nm |
| Gauge to IEC 60947-1 | B13 |
| Stranded, min. | 35 mm ² |
| Stranded, max. | 150 mm ² |
| Flexible, min. | 35 mm ² |
| Flexible, max. | 150 mm ² |
| Flexible with ferrule, min. (DIN 46228/1) | 35 mm ² |
| Flexible with ferrule, max. (DIN 46228/1) | 95 mm ² |
| AWG conductor size, min. | AWG 2 |
| AWG conductor size, max. | kcmil 300 |
| AWG conductor size, min. | 33.62 mm ² |
| AWG conductor size, max. | 85.03 mm ² |

Dimensions

| | |
|--------------------------|--------|
| Width | 32 mm |
| Height of lowest version | 118 mm |
| Length | 132 mm |
| TS 35 offset | 66 mm |

PE rating data

| | |
|------------------------------|---------------------|
| Centre screw on PE terminals | M 6 |
| PEN function | No |
| Pollution severity | 3 |
| Rated cross-section | 120 mm ² |

PE rating data

| | |
|--|--------------------------------|
| Rated impulse withstand voltage to adjacent terminal | 8 kV |
| Rated short-time current | 14400 A (120 mm ²) |
| Rated voltage for adjacent terminal | 1,000 V |
| Standards | IEC 60947-7-2 |
| Tightening torque range for fixing screw | 3.0...6.0 Nm |

UL rating data

| | |
|-------------------------|-----------|
| Min. cross-section (UL) | AWG 2 |
| Max. cross-section (UL) | kcmil 250 |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| ETIM 2.0 | EC000901 |
| ETIM 3.0 | EC000901 |
| eClass 4.1 | 27-14-03-05 |
| eClass 5.0 | 27-14-03-05 |
| eClass 5.1 | 27-14-03-05 |

Similar products

| Order No. | Part designation | Version |
|------------|------------------|--|
| 1016500000 | WPE 1.5/ZZ | Earth terminal, 1.5 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1036300000 | WDK 2.5PE | Earth terminal, 2.5 mm ² , Screw connection, Wemid, green, TS 35 |
| 1010000000 | WPE 2.5 | Earth terminal, 2.5 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1016400000 | WPE 2.5/1.5/ZR | Earth terminal, 2.5 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1010100000 | WPE 4 | Earth terminal, 4 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1905130000 | WPE 4/ZZ | Earth terminal, 4 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1905120000 | WPE 4/ZR | Earth terminal, 4 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1010200000 | WPE 6 | Earth terminal, 6 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1010300000 | WPE 10 | Earth terminal, 10 mm ² , Screw connection, Wemid, green/yellow, TS 35 |

| | | |
|------------|-----------|---|
| 1042500000 | WPE 10/ZR | Earth terminal, 10 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1010400000 | WPE 16 | Earth terminal, 16 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1010500000 | WPE 35 | Earth terminal, 35 mm ² , Screw connection, Wemid, green/yellow, TS 35 |
| 1037300000 | WPE 70/95 | Earth terminal, 95 mm ² , Screw connection, Wemid, green/yellow, TS 35 |