



General ordering data

Order No.	1964290300
Part designation	SAIL-ZW-M12BW-2/4L3.0U
Version	Twin sensor line, Connecting line, LED: Yes, 3.00 m, PUR/PVC
EAN	4032248647590
Qty.	1 pc(s).

Technical data

Ambient temperature, max.	85 °C
Ambient temperature, min.	-25 °C
Cable diameter, max.	5 mm
Cable diameter, min	4.6 mm
Connection cross-section	0.25
Contact surface	gold-plated
Contact tube diameter	M12
Core cross-section	0.25 mm ²
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	250 V DC / 300 V AC
Sheathing colour	black
Wiring diagram	
jumpered	Yes
No. of poles	3
Version	pin, straight - socket, 90°
Cable length	3 m

Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

Similar products

Order No.	Part designation	Version
1964290150	SAIL-ZW-M12BW-2/4L1.5U	Twin sensor line, Connecting line, LED: Yes, 1.50 m, PUR/PVC
1964291000	SAIL-ZW-M12BW-2/4L10U	Twin sensor line, Connecting line, LED: Yes, 10.00 m, PUR/PVC
1964290500	SAIL-ZW-M12BW-2/4L5.0U	Twin sensor line, Connecting line, LED: Yes, 5.00 m, PUR/PVC