

General ordering data	
Order No.	9457610050
Part designation	SAIL-M12G-5-0.5U
EAN	4032248762170
Qty.	1 pc(s).

Technical data	
Ambient temperature, max.	80 °C
Ambient temperature, min.	-30 °C
Cable diameter, max.	5.8 mm
Cable diameter, min	5.4 mm
Connection cross-section	0.34
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M12
Core cross-section	0.34 mm²
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	125 V
Sheathing colour	black
No. of poles	5
Version	pin, straight
Cable length	0.5 m

Similar products

Order No.	Part designation	Version
9457610030	SAIL-M12G-5-0.3U	Sensor/Actuator line, One end without connector, LED: No, 0.30 m, PUR/PVC
9457610060	SAIL-M12G-5-0.6U	Sensor/Actuator line, One end without connector, LED: No, 0.60 m, PUR/PVC

9457610090	SAIL-M12G-5-0.9U	Sensor/Actuator line, One end without connector, LED: No, 0.90 m, PUR/PVC
9457610120	SAIL-M12G-5-1.2U	Sensor/Actuator line, One end without connector, LED: No, 1.20 m, PUR/PVC
9457610150	SAIL-M12G-5-1.5U	Sensor/Actuator line, One end without connector, LED: No, 1.50 m, PUR/PVC
9457611000	SAIL-M12G-5-10U	Sensor/Actuator line, One end without connector, LED: No, 10.00 m, PUR/PVC
9457610200	SAIL-M12G-5-2.0U	Sensor/Actuator line, One end without connector, LED: No, 2.00 m, PUR/PVC
9457610250	SAIL-M12G-5-2.5U	Sensor/Actuator line, One end without connector, LED: No, 2.50 m, PUR/PVC
9457612000	SAIL-M12G-5-20U	
9457610300	SAIL-M12G-5-3.0U	Sensor/Actuator line, One end without connector, LED: No, 3.00 m, PUR/PVC
9457613000	SAIL-M12G-5-30U	
9457613500	SAIL-M12G-5-35U	
9457610400	SAIL-M12G-5-4.0U	Sensor/Actuator line, One end without connector, LED: No, 4.00 m, PUR/PVC
9457614000	SAIL-M12G-5-40U	
9457610500	SAIL-M12G-5-5.0U	Sensor/Actuator line, One end without connector, LED: No, 5.00 m, PUR/PVC
9457610600	SAIL-M12G-5-6.0U	