

PC board connectors, spring clamp connection

Spacings: 5.08 mm

wiecon


codable

2.5 mm²

Rated cross section*:
2.5 mm²

Rated current:
12 A

Connection range:
0,14 – 2.5 mm² solid / fine stranded



250 V/4 kV/3 – Overvoltage category III
400 V/4 kV/2 – Overvoltage category II
1000 V/4 kV/1 – Overvoltage category I



* When using ferrules for conductor cross section of 2.5 mm, use only ferrule no. 05.596.6127.0.

Type 8213 SUFK

Rated voltages: VDE 0110
UL ratings
CSA ratings
Approvals available soon

No. 22 – 12 AWG 300 V 12 A
No. 22 – 12 AWG 300 V 12 A

Std. pack	G	T	Poles	Part no.	Part no.	
Spacing: 5.08 mm				unmarked	marked	
100	10.16	5.08	2	25.857.3253.0	25.857.0253.0	
100	15.24	10.16	3	25.857.3353.0	25.857.0353.0	
50	20.32	15.24	4	25.857.3453.0	25.857.0453.0	
50	25.40	20.32	5	25.857.3553.0	25.857.0553.0	
50	30.48	25.40	6	25.857.3653.0	25.857.0653.0	
50	35.56	30.48	7	25.857.3753.0	25.857.0753.0	
50	40.64	35.56	8	25.857.3853.0	25.857.0853.0	
50	45.72	40.64	9	25.857.3953.0	25.857.0953.0	
50	50.80	45.72	10	25.857.4053.0	25.857.1053.0	
50	55.88	50.80	11	25.857.4153.0	25.857.1153.0	
50	60.96	55.88	12	25.857.4253.0	25.857.1253.0	
50	66.04	60.96	13	25.857.4353.0	25.857.1353.0	
50	71.12	66.04	14	25.857.4453.0	25.857.1453.0	
50	76.20	71.12	15	25.857.4553.0	25.857.1553.0	
50	81.28	76.20	16	25.857.4653.0	25.857.1653.0	
17 to 24pole upon request						
Accessories:						
Coding piece (strip)	100			05.561.9153.0		
Screwdriver DIN 5264 A 0.6 x 3.5	5			06.502.4000.0		